



DETAIL T
SCALE 20:1
TYPICAL

- 1 MATERIAL-
RECEPTACLE CONTACTS: PHOSPHOR BRONZE.
RECEPTACLE SHELL: STEEL.
PANEL MOUNT BRACKET: ZINC.
RECEPTACLE HOUSING AND TERMINATION COVERS: UL V-0 RATED THERMOPLASTIC, COLOR: BLACK.
- 2 FINISH-
RECEPTACLE CONTACTS: EITHER 0.76µm [.000030] MIN GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.76µm [.000030] MIN TOTAL IN CONTACT AREA, 1.27µm [.000050] MIN TIN-LEAD IN TERMINATION AREA, ALL OVER 1.27µm [.000050] MIN NICKEL.
RECEPTACLE SHELL: 5.08µm [.000200] MIN NICKEL OVER 1.27µm [.000050] MIN COPPER.
PANEL MOUNT BRACKET: 5.08µm [.000200] MIN NICKEL OVER 7.62µm [.000300] MIN COPPER.
- 3. RECOMMENDED WIRE:
28 AWG OR 30 AWG, SOLID OR 7 STRANDED, PVC INSULATION WITH A 0.74-0.91 [.029-.036] INSULATION DIA.
- 4 FINISH-
RECEPTACLE CONTACTS: EITHER 0.76µm [.000030] MIN GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.76µm [.000030] MIN TOTAL IN CONTACT AREA, 1.27µm [.000050] MIN TIN IN TERMINATION AREA, ALL OVER 1.27µm [.000050] MIN NICKEL.
RECEPTACLE SHELL: 5.08µm [.000200] MIN NICKEL OVER 1.27µm [.000050] MIN COPPER.
PANEL MOUNT BRACKET: 5.08µm [.000200] MIN NICKEL OVER 7.62µm [.000300] MIN COPPER.
- 5 ROHS 2002/95/EC COMPLIANT
- 6 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

5	4	15.24	42.29	52.45	41.38	46.48	34.70	30.48	50	5-750450-1
		[.600]	[1.665]	[2.065]	[1.629]	[1.830]	[1.366]	[1.200]		
6	SUPERDEDED	15.24	42.29	52.45	41.38	46.48	34.70	30.48	50	750450-1
		[.600]	[1.665]	[2.065]	[1.629]	[1.830]	[1.366]	[1.200]		
FINISH		G	F	E	D	C	B	A	NO OF POSN	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		OWN: JOHN ROOT 8-27-90 CHK: MIKE SHIRK 8-27-90		Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
0 PLC	± -	PRODUCT SPEC	108-1228			RECEPTACLE CABLE ASSEMBLY	
2 PLC	± -	APPLICATION SPEC	114-40029			W/#4-40 MOUNTING HOLES, PANEL MOUNT,	
3 PLC	± 0.13 [005]	MATERIAL		FINISH		RESTRICTED TO	
4 PLC	± -	SEE TABLE		CUSTOMER DRAWING		SCALE 5:1 SHEET 1 OF 1 REV H	