

VERSA BAR, 24V

SPECIFICATION:

Input Voltage	24 VDC
CRI	80+
Dimmable	0-10V, ELV, MLV
Beam Angle	90°
Color Temp	<div style="display: flex; justify-content: space-around;"> <div style="width: 15px; height: 15px; background-color: #f0e68c; border: 1px solid black;"></div> 3000K <div style="width: 15px; height: 15px; background-color: #add8e6; border: 1px solid black;"></div> 4300K <div style="width: 15px; height: 15px; background-color: #1e90ff; border: 1px solid black;"></div> 6250K </div>
Max Run	8 ft/driver
IP Rating	IP50 - damp locations
Mounting	Quick mount magnets included on back of bar, screws and easy flat mounting clip included
Connectors	All Versa XLR Bars include a 6" male barrel connector on one end, 6" female barrel connector on other end
Dimensions	W 0.94" (23.9mm) x H 0.39" (9.9mm)
Finish	Silver
Lens	Frosted or Clear
Warranty	1 year limited*



Certifications:



WATTAGE & LIGHT OUTPUT:

LENGTH	WATTAGE	WW LUMEN OUTPUT		NW LUMEN OUTPUT		CW LUMEN OUTPUT	
		Clear	Frosted	Clear	Frosted	Clear	Frosted
10in	3.5W	180 lm	155 lm	185 lm	159 lm	203 lm	175 lm
20in	7W	360 lm	310 lm	365 lm	314 lm	405 lm	349 lm
30in	10.5W	540 lm	465 lm	545 lm	469 lm	608 lm	523 lm
40in	14W	720 lm	620 lm	725 lm	624 lm	810 lm	698 lm
70in	24W	1260 lm	1085 lm	1265 lm	1089 lm	1418 lm	1221 lm

PART NUMBER BUILDER / ORDERING GUIDE

Example part number: VSCXLR-70-NW-24V

