



Scan the QR code and visit the product page



Code	<b>TK.LB.D0120.MEC</b>	Safety level	Danger
Dimensions (H x L)	69 mm x 140 mm (2,7" x 5,5")	Version	Standard
Material	Base in anodized aluminum 0.5 mm thickness with white background and 3.5 mm holes on the edges	Temperatures <sup>(1)</sup>	-40°C/+100°C
Applications	Machinery and control panels. Indoor and outdoor locations		
Languages <sup>(2)</sup>	Inglese		
Message <sup>(3)</sup>	<p>EN: Risk of electric shock. Orange wires inside the panel remain energized when the main switch is in the off positions. To service these circuits, shut off the equipment at the main service disconnect.</p> <p>IT: Rischio di shock elettrico. I conduttori arancioni all'interno del quadro rimangono sotto tensione quando l'interruttore principale è in posizione di spegnimento. Per operare su questi circuiti, spegnere l'apparecchiatura al sezionatore di servizio principale.</p>		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	6 pz/pcs		

(1) For indoor and outdoor exposure with high humidity. UL certification is for maximum working temperatures of +100°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.