


DXM (1.27MM PITCH) SERIES HIGH-DENSITY I/O CONNECTOR

General

DXM series high-density I/O connectors with bellow contacts are perfect for tomorrow's miniaturized electronic devices. This new 1.27mm (0.050") interconnect design ensures positive locking, effortless coupling, terminal protection and EMI reduction in a miniaturized and rugged package. DXM series offer you one of the

most varied and complete lines of High-Density connectors in the world, i.e. IDC and Solder for the plug and right angle dip, straight dip, IDC and SMT for the receptacle. Available in 14, 20, 26, 36, 50, 68, 80, 100 and 110 way.



Features

1. 1.27mm (0.050") contact spacing conserves valuable board space and permits ultra-high density designs.
2. Bellow contacts create smooth and precise mating and unmating.
3. Unique shell design assures first make/last break grounding and overall noise protection.
4. IDC termination allows quick and low cost termination to AWG #28 wires.
5. Backshell and receptacle shell are made of die-cast zinc alloy or stainless steel to reduce the penetration of external EMI noise.
6. Ferrite added to DX Right Angle Dip Type for EMI Protection is available.
7. Overmold backshell provided for ESD protection is available in 'One-Touch' locking and 'Screw' locking.
8. Termination methods are available in IDC, Soldering, Right Angle Dip, Straight Dip and SMT.

Application

Office Automation, Computers, Measurement, Communication and Control Equipment, Factory Automation, Home Automation and other commercial applications needing high density interconnections.


Specifications

Items	Standard value
Current capacity	0.5A
Rated voltage	AC125V
Insulation resistance	250M Ω or more at DC100V
Contact resistance	35m Ω or less at DC100mA
Withstanding voltage	AC 300Vrms. for 1 minute


DXM Series Variations

● One-touch lock type (14, 20, 26, 36, 50, 68 pins)




Plug cover



Plug




Receptacle




● Screw lock type (68, 80, 100, 110 pins)

Overmold cover type (100, 110 pins)



Plug cover



Plug




Receptacle




Die cast cover (68, 80, 100 pins)


Plug cover



Plug



Receptacle



Note: There is no interchangeability between the locks of the die cast cover type and overmold type.

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information. All non-Roh's products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website. Roh's search at www.hirose-connectors.com, or contact your Hirose sales representative.

1. One Touch Lock Plug Cover

Ordering Information


DX30M — 50 — CV
 (1) (2) (3)

Item	Material	Remarks
Overmold cover case	Synthetic resin, Stainless	Light beige


Material Treatment

- 1) Series number: DX30M
- 2) No. of pins: 14, 20, 26, 36, 50, 68
- 3) Cover case type
 CV: Over mold cover case

1.1 Overmold Cover



DX30M-68-CV (10)



HRS No.	Numpin	Parts No.	A				D				Applicable plug unit	Notes
			A	B	C	D	A	B	C	D		
CI.230-5051-2-10	14	DX30M-14-CV (10)	17.89	11.30	25.79	ø6.3	DX30AM-14P					
CI.230-5052-4-10	20	DX30M-20-CV (10)	20.90	14.30	29.60	ø6.7	DX30AM-20P					
CI.230-5053-2-10	26	DX30M-26-CV (10)	24.80	15.00	33.50	ø7.0	DX30AM-26P					
CI.230-5054-5-10	36	DX30M-36-CV (10)	31.06	15.75	39.80	ø8.1	DX30AM-36P					YES
CI.230-5055-8-10	50	DX30M-50-CV (10)	39.95	16.00	48.70	ø8.7	DX30AM-50P					
CI.230-5056-4-10	68	DX30M-68-CV (10)	51.38	17.27	60.13	ø7.~10.27	DX30AM-68P					


Unit: mm

General List of Engagement Combinations

Cover case and plug unit	Receptacle	
	Right angle type	Straight type
DX30M-14-CV (10) + DX30AM-14P	DX10M-14S (e), DX10GM-14SE	DX20M-14S
DX30M-20-CV (10) + DX30AM-20P	DX10M-20S (e), DX10GM-20SE	DX20M-20S
DX30M-26-CV (10) + DX30AM-26P	DX10M-26S (e), DX10GM-26SE	DX20M-26S
DX30M-36-CV (10) + DX30AM-36P	DX10M-36S (e), DX10GM-36SE	DX20M-36S
DX30M-50-CV (10) + DX30AM-50P	DX10M-50S (e), DX10GM-50SE	DX20M-50S
DX30M-68-CV (10) + DX30AM-68P	DX10M-68S (e), DX10GM-68SE	DX30M-68S

2. Plug Unit (Interchangeable One Touch-Screw Lock Type)

Ordering Information



- 1) Series No.: DX--M
- 2) Wiring style 30: Discrete cable IDC
(for fine wire use)
- 3) Applicable wire A: AWG#28
(Discrete cable press-fit type)
- 4) No. of pins: 14, 20, 26, 36, 50, 68, 80, 100, 110
- 5) Mating type P: Plug


Material Treatment




Item	Material	Remarks
Shell	Steel	Nickel plating
Insulator	PBT	Black (UL94V-0)
Male terminal	Copper alloy	Selective gold plating

Applicable

	Interface cable	
	Discrete cable fine wire type	
Conductor size	AWG#28	
Conductor composition	7/0.127	
o.d. of insulator	0.38	
Cable style	UL20276 and UL2789	
	UL2990	

2.1 Discrete Cable IDC Type (for Fine Wire)








Unit: mm

HRS. No.	Ved. pin	Parts No.	A	B	Applicable cover case		Roh's
					One touch lock type	Screw lock type	
CL230-5024-4	14	DX30A-M-14P	17.00	7.62	DX30M-14-CV (10)	—	
CL230-5025-7	20	DX30A-M-20P	20.90	11.43	DX30M-20-CV (10)	—	
CL230-5026-0	26	DX30A-M-26P	24.71	15.24	DX30M-26-CV (10)	—	
CL230-5027-2	36	DX30A-M-36P	31.06	21.59	DX30M-36-CV (10)	—	
CL230-5028-5	50	DX30A-M-50P	39.05	30.48	DX30M-50-CV (10)	—	YES
CL230-5029-8	68	DX30A-M-68P	51.38	41.96	DX30M-68-CV (10)	DX30M-68-CV2	
CL230-5030-7	80	DX30A-M-80P	59.01	49.53	—	DX30M-80-CV2	
CL230-5031-0	100	DX30A-M-100P	71.70	62.23	—	DX30M-100-CV1-2	
CL230-5064-9	110	DX30A-M-110P	78.05	68.58	—	DX30M-110-CV1	

3. One Touch Lock, Receptacle Right Angle Type

Ordering Information



- 1) Series No.: DX-M
- 2) Wiring style 10: Right angle type
- 3) Lock style (one touch lock type)
 Blank : (Receptacle case material: zinc alloy die cast)
 G : (Receptacle case material: steel)


4) No. of pins: 14, 20, 26, 36, 50, 68

- 5) Mating type S: Receptacle
- 6) Board-fitting type
 Blank : Screw on type
 E : Lock pin type
- 7) Individual specifications
 (50) : Dip portion gold plated


Material Treatment

Item	Material	Remarks
Receptacle case	Zinc alloy die cast or steel	Nickel plating
Shell	Steel	Nickel plating
Insulators	PBT	Black (UI94V-0)
Female terminal	Copper alloy	Selective gold plating

3.1 Board Screw on Type




DX10GM-68S (50)




HHS No.	Lead time	Parts No.	Unit:mm				
			A	B	C	D	E
CI.230-5224-0-50	14	DX10G1M-14-S (50)	23.64	17.14	29.54	7.62	23.64
CI.230-5177-5-50	20	DX10G1M-20-S (50)	27.43	20.95	33.35	11.43	27.45
CI.230-5526-6-50	26	DX10G1M-26-S (50)	31.28	24.76	37.16	15.24	31.26
CI.230-5226-0-50	30	DX10G1M-30-S (50)	37.61	31.11	43.51	21.50	37.61
CI.230-5227-1-50	30	DX10G1M-30-S (50)	46.50	40.00	52.40	30.48	46.50
CI.230-5181-2-50	68	DX10G1M-68S (50)	57.93	51.43	63.83	41.91	57.93

3.2 Board Lock Pin Harpoon Type





DX10G1M-50SE (50)





HHS No.	Lead time	Parts No.	Unit:mm				
			A	B	C	D	E
CI.230-5210-0-50	14	DX10G1M-14SE (50)	23.64	17.14	29.54	7.62	23.64
CI.230-5130-1-50	30	DX10G1M-20SE (50)	27.45	20.95	33.35	11.43	27.45
CI.230-5212-4-50	36	DX10G1M-26SE (50)	31.26	24.76	37.16	15.24	31.26
CI.230-5213-7-50	36	DX10G1M-36SE (50)	37.61	31.11	43.51	21.50	37.61
CI.230-5214-0-50	50	DX10G1M-36SE (50)	46.50	40.00	52.40	30.48	46.50
CI.230-5134-2-50	68	DX10G1M-68SE (50)	57.93	51.43	63.83	41.91	57.93

3.3 Board Lock Pin Round Type




DX10M-68SE (50)



HRS. No.	Mod./Pin	Parts No.	A	B	C	D	E	RoHS
CI.230-5107-4-50		DX10M-14SE (30)	23.64	17.14		7.62		
CI.230-5067-7-50	20	DX10M-20SE (30)	27.45	20.95	33.35	11.43	27.45	
CI.230-5068-0-50		DX10M-26SE (30)	31.26	24.76	37.16	15.24	31.26	YES
CI.230-5069-2-50	36	DX10M-36SE (30)	37.61	31.11	43.51	21.50	37.61	
CI.230-5070-1-50	50	DX10M-50SE (30)	46.50	40.00	52.40	30.48	46.50	
CI.230-5071-4-50	68	DX10M-68SE (30)	57.93	51.43	63.33	41.91	57.93	


Unit:mm

PCB Layout (Recommended board thickness:1.6mm)



(20, 36, 68 pins)

- ① Contact No.1
 - ② Contact No.2
 - ③ Contact No.3
 - ④ Contact No.(N-2)
 - ⑤ Contact No.(N-1)
 - ⑥ Contact No.(N)
- *N: Numbers of Pin




(14, 26, 50 pins)

- ① Contact No.1
 - ② Contact No.2
 - ③ Contact No.3
 - ④ Contact No.(N-2)
 - ⑤ Contact No.(N-1)
 - ⑥ Contact No.(N)
- *N: Numbers of Pin

No. of pin	A	B
14	7.62	23.64
20	11.43	27.45
26	15.24	31.26
36	21.50	37.61
50	30.48	46.50
68	41.91	57.93

Unit:mm

Panel-Fitting Dimensional Drawing (Recommended panel thickness:max. 1.6mm)




No. of pin	A	B
14	23.64	19.99
20	27.45	23.80
26	31.26	27.60
36	37.61	33.90
50	46.50	42.80
68	57.93	54.23

Unit:mm

5. One Touch Lock, Receptacle Straight Type

Ordering Information




- 1) Series number: DX-M
- 2) Wiring style
- 20: Straight dip
- 3) Lock style
- Blank: One Touch Lock Type

- 4) Number of positions: 14, 20, 26, 36, 50, 68
- 5) Type of aperture
- S: Receptacle connector
- 6) Individual specifications
- (50): Dip portion gold plated



Material Treatment

Item	Material	Remarks
Receptacle case	Zinc alloy die cast	Nickel plating
Shell	Steel	Nickel plating
Insulators	PBT resin	Black (01,94V-0)
Female terminal	Copper alloy	Selective gold plating


5.1 Receptacle Straight Type



DX20M-68S (50)



Connector mounting condition




Note: Fasten the printed circuit board with screws using a tightening torque of 0.3 to 0.4 N.m.

HMS No.	No. of pin	Parts No.	A	B	C	D	Radii
CL230-5012-50	14	DX20M-14S (50)	7.02	17.14	28.34	29.64	
CL230-5013-50	20	DX20M-20S (50)	11.43	20.05	33.35	37.45	
CL230-5014-50	26	DX20M-26S (50)	15.24	24.76	37.16	37.20	YES
CL230-5015-3-50	36	DX20M-36S (50)	21.59	31.11	43.31	37.61	
CL230-5016-6-50	50	DX20M-50S (50)	30.48	40.00	52.40	46.50	
CL230-5017-4-50	68	DX20M-68S (50)	41.91	51.43	63.83	57.93	

Unit: mm

PCB Layout (Recommended board thickness: 1.6mm)




(20, 36, 68 pins)

- ① Contact No.1
 - ② Contact No.2
 - ③ Contact No.3
 - ④ Contact No.(N-2)
 - ⑤ Contact No.(N-1)
 - ⑥ Contact No.(N)
- *N: Numbers of Pin

Unit: mm

No. of pin	A	B
20	11.43	27.45
36	21.59	37.61
68	41.91	57.93

Panel-Fitting Dimensional Drawing (Recommended panel thickness: max. 1.6mm)




(14, 26, 50 pins)

- ① Contact No.1
 - ② Contact No.2
 - ③ Contact No.3
 - ④ Contact No.(N-2)
 - ⑤ Contact No.(N-1)
 - ⑥ Contact No.(N)
- *N: Numbers of Pin

Unit: mm

No. of pin	A	B
14	37.61	33.90
26	46.50	42.80
68	57.93	54.23




Unit: mm

No. of pin	A	B
14	23.64	19.99
20	27.45	23.8
26	31.26	27.6
36	37.61	33.9
50	46.50	42.8
68	57.93	54.23

6. One Touch Lock Receptacle Flat Ribbon Cable Type

Ordering Information



- 4) No. of pins 36, 50, 68
- 5) Mating type
S: Receptacle
- 6) Individual specifications
(50):Dip portion gold plated

Material Treatment

Item	Material	Remarks
Receptacle case	Zinc alloy die cast	Nickel plating
Shell	Steel	Nickel plating
Insulators	PBT resin	Black (UL94V-0)
Female terminal	Copper alloy	Selective gold plating

- 1) Series No.: DX--M
- 2) Connector style
33: Flat IDC type
(for ribbon cable use)
- 3) Applicable cable
A: AWG#28


6.1 Receptacle, Flat Ribbon Cable Type

DX33AM-68SS (50)

HTS No.	RoHS pin	Parts No.	A	B	C	D	RoHS
CI.230-5092-2-50	36	DX33AM-68S (50)	31.11	43.51	21.59	37.61	
CI.230-5092-4-50	50	DX33AM-68S (50)	40.00	52.40	30.48	46.50	YIS
CI.230-5092-3-50	68	DX33AM-68S (50)	51.42	63.83	41.91	57.03	

Unit: mm

Panel-Fitting Dimensional Drawing
 (Recommended panel thickness: max. 1.6mm)



Unit: mm		
No. of pin	A	B
36	37.61	33.90
50	46.50	42.80
68	57.93	54.23

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
 All non-Roh's products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website Roh's search at www.hirose-connectors.com, or contact your Hirose sales representative.

7. Screw Lock Type, Plug Cover

Ordering Information


DX30M — 110 — CV1
 (1) — (2) — (3)

- 1) Series No.: DX30M
 - 2) No. of pins: 68, 80, 100, 110
 - 3) Cover case type
- CV1: Overmold cover case
 CV2: Die cast cover


Material Treatment

Item	Material	Remarks
Overmold cover	Stainless steel, Synthetic resin	Dark grey
Die cast cover	Zinc alloy die cast	Silver coated


1.1 Overmold Cover




DX30M-100-CV1



DX30M-110-CV1



HRS No.	Part No.	Roh's
CI290-30937	DX30M-100-CV1	Y/S




HRS No.	Part No.	Roh's
CI290-30833	DX30M-110-CV1	Y/S

List of Engagement Combinations


Cover case and plug unit	Receptacle	Ferrite core type
DX30M-100-CV1 + DX30AM-100P	DX10AM-100SE2 (50), DX10AV-100SE1 (50)	DX10AMF-100SE1 (50)
DX30M-110-CV1 + DX30AM-110P	DX10AM-110SE2 (50), DX10AV-110SE1 (50)	—

The product information in this catalog is for reference only. Please request the Engineering Drawing for the most current and accurate design information.
 All non-Rohs products have been discontinued, or will be discontinued soon. Please check the products status on the Hirose website Rohs search at www.hirose-connectors.com, or contact your Hirose sales representative.

7.2 Die Cast Cover



DX30M-48-CV2



HRS No.	No. of pin	Parts No.	A	B	C	Applicable plug unit			Rohs
						IDC type	DC type		
CL230-503949	68	DX30M-48-CV2	11.00	64.93	46.68		DX30AM-48P		
CL230-503948	80	DX30M-80-CV2	12.50	72.55	57.30		DX30AM-80P		YFS
CL230-506140	100	DX30M-100-CV2	14.00	85.25	70.00		DX30AM-100P		

Unit: mm

List of Engagement Combinations

Cover case and plug unit	Hermetic		
	Right angle type	Straight DIP type	Ribbon cable type
DX30M-48-CV2+DX30AM-48P	DX103M-48S (50), DX103M-48SE (50)	DX203M-48S (30)	DN33AM-48S-LVA (30)
DX30M-80-CV2+DX30AM-80P	DX103M-80S (50), DX103M-80SE (50)	DX203M-80S (30)	—
DX30M-100-CV2+DX30AM-100P	DX103M-100S (50), DX103M-100SE (50)	DX203M-100S (30)	—

8. Screw Lock, Receptacle Right Angle Type

Ordering Information

DX 10 B M — 68 S E (50)
 (1) (2) (3) (1) (4) (5) (6) (7)


- 1) Series No.: DX-M
- 2) Connector style 10: Right angle type
- 3) Lock style (Screw lock type)
 - A: Receptacle case material — Steel
 - B: Receptacle case material — Zinc alloy die cast
- 4) No. of pins: 68, 80, 100, 110

- 5) Mating type S: Receptacle
- 6) Board fitting type
 - Blank : Screw on type
 - E : Lock pin round type
 - E1 : Lock pin harpoon type (Board thickness 1.6mm)
 - E2 : Lock pin harpoon type (Board thickness 1.2mm)
- 7) Individual specifications
 - (50) : Dip portion gold plated

Material Treatment

Item	Material	Remarks
Receptacle case	Zinc alloy die cast or steel	Nickel plating
Shell	Steel	Nickel plating
Insulators	PBT resin	Black (UL94V-0)
Female terminal	Copper alloy	Selective gold plating

8.1 Board Screw on Type




DX10BM-68S (50)

HRS No.	No. of pins	Parts No.	A	B	C	D	Roh's
CL230-5008-50	68	DX10BM-68S (50)	57.03	63.83	41.91	57.03	
CL230-5000-50	80	DX10BM-80S (50)	65.53	71.45	49.23	65.53	YES
CL230-5010-50	100	DX10BM-100S (50)	78.23	84.15	62.23	78.23	

Unit: mm

8.2 Board Lock Pin Harpoon Type




DX10AM-110SE2 (50)

HRS No.	No. of pins	Parts No.	A	B	C	D	E	Roh's
CL230-5137-50	100	DX10AM-100SE2 (50)	78.25	84.15	62.23	78.25	2.7	
CL230-5080-50	100	DX10AM-100SE1 (50)	78.25	84.15	62.23	78.25	3.4	YES
CL230-5138-50	110	DX10AM-110SE2 (50)	84.00	90.30	68.38	84.00	2.7	
CL230-5088-50	110	DX10AM-110SE1 (50)	84.00	90.30	68.38	84.00	3.4	

Unit: mm

11. Screw Lock Receptacle Straight Type

Ordering Information



- 1) Series No.: DX--M
- 2) Connector style
20: Straight dip
- 3) Lock style
B: Screw lock type

- 4) No. of pins: 68, 80, 100
- 5) Mating type
S: Receptacle
- 6) Individual specifications
(50): Dip portion gold plated

Material Treatment

Item	Material	Remarks
Receptacle case	Zinc alloy die cast	Nickel plating
Shell	Steel	Nickel plating
Insulator	PBT resin	Black (UL94V-0)
Female terminal	Copper alloy	Selective gold plating


11.1 Receptacle Straight Type

DX20BM-80S (50)


THNS No.	No. of pin	Parts No.	A	B	C	RoHS
CI.230-5020-3-50	68	DX20BM-68S (50)	41.91	63.83	57.93	
CI.230-5021-6-50	80	DX20BM-80S (50)	49.53	71.45	65.55	YES
CI.230-5022-9-50	100	DX20BM-100S (50)	62.23	84.15	78.25	

Unit: mm

PCB Layout (Recommended Board Thickness:1.6mm)



Panel-Fitting Dimensional Drawing



● DX20BM

Panel thickness	No. of washers
0~0.4	2
1.05~1.2	1
1.16~2	No washer

Unit: mm

No. of pin	A	B
68	57.93	54.23
80	65.55	61.85
100	78.25	74.55

12. Screw Lock Receptacle, Flat Ribbon Cable Type

Ordering Information

DX 33 A M — 68 S LNA (50)

(1) (2) (3) (1) (4) (5) (6) (7)


- 5) Mating type
- S: Receptacle
- 6) Board fitting type
- LNA: Screw lock type
- 7) Individual specifications
- (50) : Dip portion gold plated

Material Treatment


Item	Material	Remarks
Receptacle case	Zinc alloy die cast	Nickel plating
Shell	Steel	Nickel plating
Insulator	PBT resin	Black (UL94V-0)
Female terminal	Copper alloy	Selective gold plating

- 1) Series No.: DX--M
- 2) Connector style
- 33: Flat IDC type (for ribbon cable)
- 3) Applicable wire
A: AWG#28
- 4) No. of pins: 68

12.1 Receptacle, Flat Ribbon Cable Type



Panel-Fitting Dimensional Drawing




● DX33AM

Panel thickness	No. of washers
0~0.4	2
0.8~1.2	1
1.6~2	No washer

13. Plug Straight Type

Ordering Information




- 1) Series No.: DX--M
- 2) Connector style
20E: Straight dip
- 3) No. of pins: 110
- 4) Mating type
P: Plug

Material Treatment

Item	Material	Remarks
Shell	Steel	Nickel plating
Insulator	PBT resin	Black (1L9/V-0)
Male contact	Copper alloy	Selective gold plating

13.1 Plug Straight Type



PCB Layout (Recommended Board Thickness:1.5mm)






Diagram of Mounting Conditions for DX20EM

Note: Secure the connectors and boards of this product to the panel.




Panel-Fitting Dimensional Drawing (Recommended Panel Thickness:Max.1.5mm)




List of Engagement Combinations

Plug straight type	Receptacle right angle type
DX20EM-110P	DX10AM-10SE1 (50) or DX10AM-10SE2 (50)


Connecting Method (Discrete Cable IDC Type) Connecting Tools




Cable distribution jig




Cable shearing unit




Shield case fixing jig



IDC press



IDC guide plate unit



Hood insertion jig

List of Connecting Jigs and Accessories Plug Connector

Plug Connector

Cable	Connector Name	Cable Distribution	Process			Shield case fixing Order attachments separately ※1	Hood insertion Order attachments separately ※2
			Press	Crimping	Remaining Part cutting		
L/O Cable (Discrete wire)	DX30AM-14P	By hand DX30AM-CAT1 CL902-200A-0					
	DX30AM-20P						
	DX30AM-26P						
	DX30AM-36P						
	DX30AM-50P						
	DX30AM-68P						
	DX30AM-80P						
	DX30AM-100P						
	DX30AM-110P						
							Other attachments separately ※3

※1 DX30AM-CCT1 (61) CL902-0213-8 (61) *2 DX30AM-HP-T1-14 CL902-0217-9 *4 DX30AM-HP-T1-110 CL902-0219-4
DX30AM-CCT1 (62) CL902-0213-8 (62) *3 DX30AM-HP-T1-100 CL902-0218-1

Receptacle Connector

Cable	Connector Name	Press	Guide plate
Ribbon Cable	DX33AM-68SLNA (50)	Hi-Flex Connecting press EHP-P02 CL50-0082-2	DX33AM-GP/A (Come with pressure block) CL902-0235-5
	DX30AM-100P		