

White High-Intensity LED Lamp (3 mm, 40° Viewing Angle)



OVLAW4CB7

Features:

- High luminous intensity
- Through-hole type
- Clear lens
- High efficiency




Description:

The OVLAW4CB7 is a round 3mm white high-intensity through-hole lamp with a 40° viewing angle. It is designed for wide-angle uniform light output.

Applications:

- Indicators for medical, industrial, consumer and office equipment
- Indicators for white goods and home appliances
- Interior and exterior architectural and accent lighting
- Signs and digital information displays, video screen non-color and RGB presentation
- Automotive backlighting and indicators

| Part Number | Material | Emitted Color | Intensity Typ. mcd | Lens Color |
|-------------|----------|---------------|--------------------|------------|
| OVLAW4CB7 | InGaN | White | 6200 | Clear |



RoHS



DO NOT LOOK DIRECTLY AT LED WITH UNSHIELDED EYES OR DAMAGE TO RETINA MAY OCCUR.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

White High-Intensity LED Lamp (3 mm, 40° Viewing Angle)



OVLAW4CB7

Electrical Specifications

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| | |
|---|---------------|
| Storage Temperature Range | -40 ~ +100° C |
| Operating Temperature Range | -40 ~ +100° C |
| Reverse Voltage | 5 V |
| Power Dissipation | 100 mW |
| Average Forward Current | 25 mA |
| Peak Forward Current (Duty Ratio = 1/10, Pulse Width = 0.1ms) | 100 mA |
| Current Linearity vs Ambient Temperature | -0.29 mA/° C |
| LED Junction Temperature | 125° C |
| Electrostatic Discharge Classification (JEDEC-JESD22-A114F) | Class 1C |
| Lead Soldering Temperature (5 seconds maximum) | 260° C |
| Lead Soldering Temperature (5 seconds maximum) | 260° C |

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|-------------------------|--------------------------|-------|-------|------|---------------|----------------------|
| I_V | Luminous Intensity | 4,360 | 6,200 | ---- | mcd | $I_F = 20\text{ mA}$ |
| $2\theta_{\frac{1}{2}}$ | 50% Power Angle | ---- | 40 | ---- | deg | $I_F = 20\text{ mA}$ |
| V_F | Forward Voltage | ---- | 3.2 | 4.0 | V | $I_F = 20\text{ mA}$ |
| I_R | Reverse Current | ---- | ---- | 10 | μA | $V_R = 5\text{ V}$ |
| x | Chromaticity Coordinates | ---- | 0.31 | ---- | ---- | $I_F = 20\text{ mA}$ |
| y | Chromaticity Coordinates | ---- | 0.32 | ---- | ---- | $I_F = 20\text{ mA}$ |

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

White High-Intensity LED Lamp (3 mm, 40° Viewing Angle)



OVLAW4CB7

Typical Electro-Optical Characteristics Curves




Fig. 1 Forward Current vs Forward Voltage



Fig. 2 Luminous Intensity vs. Forward Current



Fig. 3 Reverse Current vs. Reverse Voltage I_R (μ A)




Fig. 4 Allowable Forward Current vs. Ambient Temperature




Fig. 5 Luminous Intensity at $I_F = 20$ mA vs. Ambient Temperature




Fig. 6 Relative Luminous Intensity vs. Wavelength

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

White High-Intensity LED Lamp (3 mm, 40° Viewing Angle)



OVLAW4CB7

Beam Pattern




Soldering:

Soldering heat may damage the LED. Careful attention should be paid during the soldering process and PCB assembly. In order to eliminate the stress of heat shock, please solder the LEDs no closer than 3mm from the base of the epoxy bulb.

Recommended Soldering Conditions:

| | Wave Soldering | Manual Solder Dipping | Hand Soldering by Iron |
|----------------------|----------------|-----------------------|------------------------|
| Pre-heat Temperature | 105°C Max | | |
| Pre-heat Time | 30 seconds Max | | |
| Peak Temperature | 250°C Max | 260°C Max | 350°C Max |
| Dwell Time | 3 seconds Max | 5 seconds Max | 3 seconds Max |

Packaging: 500 pcs per bulk bag



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

White High-Intensity LED Lamp (3 mm, 40° Viewing Angle)



OVLAW4CB7

Reliability Test

LED lamps are checked by reliability tests based on MIL standards.

1. Test Conditions, Acceptable Criteria & Results:

| Classification | Test Item | Standard Test Method | Test Conditions | Duration | Unit | Acc / Rej Criteria | Result |
|------------------|----------------------------------|----------------------------|--|------------|------|--------------------|--------|
| Life Test | Operation Life Test (OLT) | MIL-STD-750D Method 1026.3 | $T_A=25^{\circ}\text{C}$, $I_F=30\text{mA}$ * | 1000 Hrs | 100 | 0 / 1 | Pass |
| Environment Test | High Temperature Storage (HTS) | MIL-STD-750D Method 1032.1 | $T_A=100^{\circ}\text{C}$ | 1000 Hrs | 100 | 0 / 1 | Pass |
| | Low Temperature Storage (LTS) | MIL-STD-750D Method 1032.1 | $T_A=-40^{\circ}\text{C}$ | 1000 Hrs | 100 | 0 / 1 | Pass |
| | Temp. & Humidity with Bias (THB) | MIL-STD-750D Method 103B | $T_A=85^{\circ}\text{C}$, $R_h=85\%$ $I_F=20\text{mA}$ ** | 500 Hrs | 100 | 0 / 1 | Pass |
| | Thermal Shock Test (TST) | MIL-STD-750D Method 1056.1 | 0°C ~ 100°C 2min 2min | 100 cycles | 100 | 0 / 1 | Pass |
| | Temperature Cycling Test (TCT) | MIL-STD-750D Method 1051.5 | -40°C ~ 25°C ~ 100°C ~ 25°C 30min 5min 30min 5min | 100 cycles | 100 | 0 / 1 | Pass |
| Mechanical Test | Solderability | MIL-STD-750D Method 2026.4 | $235\pm 5^{\circ}\text{C}$, 5 sec | 1 time | 20 | 0 / 1 | Pass |
| | Resistance to Soldering Heat | MIL-STD-750D Method 2031.1 | $260\pm 5^{\circ}\text{C}$, 5 sec | 1 time | 20 | 0 / 1 | Pass |
| | Lead Integrity | MIL-STD-750D Method 2036.3 | Load 2.5N (0.25kgf) 0° ~ 90° ~ 0° , bend | 3 times | 20 | 0 / 1 | Pass |

Remark : (*) $I_F=30\text{mA}$ for AlInGaP chip ; $I_F=20\text{mA}$ for InGaN chip

(**) $I_F=20\text{mA}$ for AlInGaP chip ; $I_F=10\text{mA}$ for InGaN chip

2. Failure Criteria ($T_A=25^{\circ}\text{C}$):

| Test Item | Symbol | Test Conditions | Criteria for Judgment | |
|--------------------|--------|--------------------|-----------------------|--------------------|
| | | | Min. | Max. |
| Luminous Intensity | I_V | $I_F=20\text{ mA}$ | $LSL \times 0.7$ ** | |
| Forward Voltage | V_F | $I_F=20\text{ mA}$ | | $USL \times 1.1$ * |

(*) USL : Upper Standard Level , (**) LSL : Lower Standard Level

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com