



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 3. Beryllium Copper
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. Teflon

RoHS Compliant

Remark:
 1. Max. Panel Thickness = .256 (6.5)

Dimensions are in Inches				Part No.	
Unless Otherwise Specified Tolerances				Approved	
0.5-6 = ±0.2				Date	
6-30 = ±0.4				7-10-2015	
30-120 = ±0.6				Checked	
120-315 = ±1				Date	
315-1000 = ±1.6				7-10-2015	
1000-2000 = ±2.4				Drawn	
				Date	
				7-10-2015	

NTE Electronics

Title
 SMA Bulkhead Jack to Jack Adapter

Drawing No. 06-S007

File No.

No	Description	Material	Finish	Q'ty	Drawing No.
5	Hex-Nut	Note 1	Note 2	1	
4	Lock Washer	Note 1	Note 2	1	
3	Contact Pin	Note 3	Note 4	1	
2	Insulator	Note 5	Natural	2	
1	Body	Note 1	Note 2	1	

A

A