

記號 MARK	ECN NO.	日期 DATE	修改 DRAW	核准 APPROVE

FEATURES:

1 Electrical Test:

- A. Safety Voltage/Current Rating 150V ac, at 1.5A.
- B. Dielectric with standing 1000V/DC/min, <0.5A.
- C. Insulation Resistance: >500M Ω, 1000V./min
- D. Contact Resistance: <20M Ω

2 Mechanical:

- A. Cable-to-Plug tensile strength-20LBs(89N)min.
- B. Durability:750 mating cycles.
- 3 Operation Temperature:-20℃~+80℃.
- 4. Environmental compliance
- A. the products are compliant with the RoHS, and REACH ETC.
- 5. Safety standards:UL E239590



EASE ELECTRONICS CO., LIMITED


品名规格 DESCRIPTION	CONN MOD PLUG 8P8C UNSHIELDED CAT5E			页次 SHEET	1/1
产品编号 PRODUCT NO	RJ45-5U	单位 UNIT	mm	比例 SCALE	1:1
		版本 EDITI		A/0	

DIMENSION IN mm(Inch)	
TOLERANCE UNLESS OTHERWISE SPECIFIED	
x. x	±0.2
x. xx	±0.1
x. xxx	±0.05

第三视角法  
THIRD ANGLE PROJECTION

制图 DRAWN	王辉	日期 DATE	2023.02.10
核对 CHECK	李勇波	日期 DATE	2023.02.10
批准 APPRO	夏赞华	日期 DATE	2023.02.10

铜片规格



胶壳 PC(聚碳酸酯)	<input type="checkbox"/> 94-V0	<input checked="" type="checkbox"/> 94-V2	1	
金片 (PIN针) Contacts	<input checked="" type="checkbox"/> 黄铜 Brass	<input type="checkbox"/> 磷铜 Phosphor copper	8	
	<input type="checkbox"/> G/F"	<input type="checkbox"/> 1u"	<input type="checkbox"/> 3u"	<input type="checkbox"/> 6u"
	<input type="checkbox"/> 15u"	<input type="checkbox"/> 30u"	<input type="checkbox"/> 50u"	<input type="checkbox"/> S"