GlobTek, Inc.	Drawing Title: High Current Power DIN Jack Jack, 4 Circuit		
www.globtek.com	Model No. Connector		
186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Part No./Ordering No. JACKPWRDIN4L	Rev A1	

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at http://www.globtek.com/iso-certificates/

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (http://en.globtek.com/terms-and-conditions/).

Prop 65 Statement: https://en.globtek.com/prop-65-statement.pdf

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing. A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:


PROPRIETARY INFORMATION


PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/03/2023 12:06:41 PM CLONED FROM JACKPWRDIN3L


GlobTek, Inc.	Drawing Title: High Current Power DIN Jack Jack, 4 Circuit		
www.globtek.com	Model No. Connector		
186 Veterans Drive,			
Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. JACKPWRDIN4L	Rev A1	
Fax (201) 784-0111			

		RE	VISIO	N HISTORY		
REV	DESCRIPTION	S	UB	DATE	APPROVED	
A1	Recover drawing	Q)A	07/12/2021	QA	
А	Initial release	D	R	12/07/2020	DAVID	
AGENCY OF	NLINE DOCUMENTS					
RoHS/RoHS3 Declaration https://www.globtek.com/pdf/rohs_cert/01t3a000005Csh9AAC						
REACH Dec	REACH Declaration https://www.globtek.com/pdf/iso_certificates/REACH.pdf					
Conflict Mine	nflict Minerals Declaration https://www.globtek.com/pdf/conflict-minerals.pdf					
Prop 65 Statement <u>https://en.globtek.com/prop-65-statement.pdf</u>						
IPXY rating i	s based on 3rd party testing	and customers should	l check s	uitability and test system level IPX	Y rating before ordering.	

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before orderin Mechanical Specifications:







PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/03/2023 12:06:41 PM CLONED FROM JACKPWRDIN3L

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111

Part No./Ordering No. JACKPWRDIN4L

Model No. Connector

4	Round shell	Brass:0.35mm	D. Cu/Sn	1
3	Thick Pin	Brass:0.28mm	D. Cu/Sn	4
2	Rear cover	PBT	BLACK	1
1	Foundation bed	PBT	BLACK	1
NO.	DFSCRIPTION	MATFRIAL	REMARKS	QTY

Electrical Specifications:

1. Current Rating: 7.5A/ Pin

2. Rated Voltage: 56V

3. Contact Impedance: 30mOhm MAX

4. Insulation Resistance: 100MOhm MIN,500V DC

5. Withstanding Voltage: 250V AC(50Hz) for one minute

6. Operating Temperature: -25-75°C

7. Mating & unmating Force: 5~35N

8. Durability: 5000 Cycles

SZ SKU:430-04641003(R) Mates with: KPPX-4P, KPPX-4P-SR7DI, PDP-40 Equal to: KPJX-4S, PD-40

Rev A1

Drawing Title: High Current Power DIN Jack Jack, 4 Circuit

GlobTek, Inc.	Drawing Title: High Current Power DIN Jack Jack, 4 Circuit	
www.globtek.com	Model No. Connector	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. JACKPWRDIN4L	Rev A1
Fax (201) 784-0111		

PACKAGING

Packing Spec P/N:	
Box Qty:	TBD
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	TBD
Master Carton Cubic Volume (m ³):	0.00
Master GW (Kg):	kg
wt Ea. (Kg):	kg
wt Ea. (Kg):	kg
LABEL SPECS: ,	
PACK SPEC:	

PROPRIETARY INFORMATION PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023

guest /08/03/2023 12:06:41 PM CLONED FROM JACKPWRDIN3L