

AirPrime® FX30 Certified Cellular Modems: *All FX30 units ship with DC power supply. If customer wants an AC power supply, use PN: PWR-12VDC-1.5A-FX30*



- Carrier-certified modem (Global)
- Programmable Yocto Linux
- LTE Cat M1/NB-IOT w/ 2G FB & GNSS
- 300 Kbps DL / 375 Kbps UL
- USB/Serial or USB/Ethernet interface
- Features Sierra WP7702
- Class 1, Div 2 and UL

FX30S_1104542 (Serial) | FX30_1104534 (Ethernet)

75 x 60 x 32 mm



- Carrier-certified modem (EMEA)
- Programmable Yocto Linux
- LTE Cat 1 w/ 2G & 3G FB & GNSS
- 10 Mbps DL / 5 Mbps UL
- USB/Ethernet interface
- Features Sierra WP7607-1
- Class 1, Div 2 and UL

EMEA: FX30_1104627 (Ethernet-Only Version)

75 x 60 x 32 mm



- Carrier-certified modem (NA)
- Programmable Yocto Linux
- LTE Cat 1 w/ 2G & 3G FB & GNSS
- 10 Mbps DL / 5 Mbps UP
- USB/Ethernet interface
- Features Sierra WP7611
- Class 1, Div 2 and UL

NA: FX30S_1104779 (Serial-RS232) | FX30_1104778 (Ethernet)

75 x 60 x 32 mm