



## Data Sheet | Item Number: 2787-2154

Power supply; Pro 2; 1-phase; 48 VDC output voltage; 2.5 A output current; Top-Boost + PowerBoost; communication capability

<https://www.wago.com/2787-2154>



### Features:

- Power supply with TopBoost, PowerBoost and configurable overload behavior
- Configurable digital signal input and output, optical status indication, function keys
- Communication interface for configuration and monitoring
- Optional connection to IO-Link, EtherNet/IP, Modbus TCP or Modbus RTU
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Pluggable connection technology
- Electrically isolated output voltage (SELV/PELV) per EN 61010-2-201/UL 61010-2-201
- Marker slot for WAGO marking cards (WMB) and WAGO marking strips

### Technical data

Input	
Phases	1
Nominal input voltage $U_{i, nom}$	1 x AC 100 ... 240 V
Input voltage range	1 x AC 90 ... 264 V; DC 130 ... 240 V
Nominal mains frequency range	50 ... 60 Hz
Input current $I_i$	$\leq 1.3$ A (240 VAC; nominal load)
Inrush current	$\leq 11$ A (after 1 ms)
Power factor correction (PFC)	active

Output	
Nominal output voltage $U_{o, nom}$	DC 48 V (SELV)
Output voltage range	DC 48 ... 56 V (adjustable)
Default setting	DC 48 V
Nominal output current $I_{o, nom}$	2.5 A (48 VDC)
Nominal output power	120 W
Deviation	$\leq 1$ %
Residual ripple	$\leq 70$ mV (Peak-to-peak)
Current limitation	$1.1 \times I_{o, nom}$ (typ.)
Overload behavior	TopBoost/PowerBoost/Time-limited constant current mode (other overload behaviors can be set)

### Output

PowerBoost	DC 7.5 A (5 s)
TopBoost	up to 600 %

### Signaling and Communication

Signaling	Optical status indication (DC OK; load; warning and error states) Digital signal input and output (DI/DO)
Communication	USB (Communication Cable 750-923) Ethernet/IP (Communication Module 2789-9023) IO-Link (Communication Module 2789-9080) Modbus RTU (Communication Module 2789-9015) Modbus TCP (Communication Module 2789-9052)

### Efficiency/power losses

Power loss $P_1$	$\leq 0.8$ W (Standby); $\leq 1.7$ W (No load); $\leq 9$ W (230 VAC; nominal load)
Efficiency (typ.)	95.3 %

### Circuit protection

Internal fuse	T 6.3 A / 250 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	16 A (for USA/Canada: 15 A)

### Safety and protection

Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	DC 0.5 kV
Isolation voltage (sec.-signal)	DC 0.5 kV
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	III ( $\leq 2000$ m a.s.l.); II ( $> 2000$ m a.s.l.)
Pollution degree	2
Transient suppression (primary)	Yes
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	$> 900,000$ h (per IEC 61709)

### Connection data

Connection type 1	Input/output/signaling
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 721 Series
Solid conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	2.5 ... 1.5 mm <sup>2</sup> / 12 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule	1.5 ... 0.08 mm <sup>2</sup> / 16 ... 28 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches

### Physical data

Width	35 mm / 1.38 inches
Height	130 mm / 5.118 inches
Depth from upper-edge of DIN-rail	130 mm / 5.118 inches
Note (dimensions)	Height without connector Height with connector: 166 mm

### Mechanical Data

Mounting type	DIN-35 rail
---------------	-------------

### Material Data

Fire load	0 MJ
Weight	650 g

### Environmental requirements

Ambient temperature (operation at $U_N$ )	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Surrounding air temperature (storage)	-40 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	See instruction leaflet
Operating altitude (max.)	5000 m

### Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201

### Commercial data

ETIM 8.0	EC002540
ETIM 7.0	EC002540
PU (SPU)	1 pcs
Country of origin	CN
GTIN	4066966121384
Customs tariff number	85044083900

### Approvals / Certificates

#### General approvals



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 61010-2-201	E255817

#### Approvals for hazardous areas



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	E198726

### Downloads

### Environmental Product Compliance

**Compliance Search**

Environmental Product Compliance 2787-2154

**Documentation**

**Manual**

Product Manual Power supply; Pro 2; 1-phase; 48 VDC output voltage; 2.5 A output current;	V 1.0.2 18.02.2022	pdf 8064.47 KB	
---	-----------------------	-------------------	--

**Bid Text**

2787-2154	11.05.2022	docx 32.35 KB	
2787-2154	11.05.2022	xml 8.72 KB	

**Instruction Leaflet**

Power supply; Pro 2; 1-phase; 48 VDC output voltage; 2.5 A output current;	V 1.0.0 03.05.2021	pdf 4297.35 KB	
--	-----------------------	-------------------	--

**CAD/CAE-Data**

**CAD data**

2D/3D Models 2787-2154	
---------------------------	--

**1 Compatible Products**

**1.1 Optional Accessories**

**1.1.1 Communication**

**1.1.1.1 Communication module**

<b>Item No.: 2789-9023</b> Communication module; EtherNet/IP; communication capability	<b>Item No.: 2789-9080</b> Communication module; IO-Link; communication capability	<b>Item No.: 2789-9015</b> Communication module; Modbus RTU; RJ45; communication capability	<b>Item No.: 2789-9052</b> Communication module; Modbus TCP; communication capability

**1.1.2 Marking**

**1.1.2.1 Marker carrier**

**Item No.: 2789-1233**  
Marker carrier; for WMB or marking strips; Length: 33 mm

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)