



**Electrical**

Operating voltage : 250VAC max.

Current rating: 3Amps max.

Insulation resistance: 1000 Mohms min 500VDC

Dielectric withstanding voltage: 1000VAC for 1MINIUTE

Operating temperature: -55c to +105c

6	UL1007 26AWG INSULATOR WIRE,	25	M541
5	PCB: SAK-7	1	M730
	ELECTRO-PLATED HOOD	1SET	M16
4	SCREW 4*12.5mm, #4-40,WITH PAD,ASSEMBLY TYPE	4	M95
3	HEX-NUT 5*6.6mm	2	M95
2	DB25 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
1	DB25 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
No.	DESCRIPTION	Q'TY	Supplier

**RoHS compliant**

Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	11.08.2014	Joanna
X.	±1					Approved	14.05.2020	Winnie
X.X	±0.20							
DIM	TOL	①	Update	14.05.2020	Winnie			
		②	Drawn	11.08.2014	Joanna			
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No. <b>AB972</b>	
Drawing-No. <b>ASS 7208 CA</b>	rev01
Replace	Sheet

