


SMT Power Inductor

High Current Composite Inductor - PA5430.XXXNLT and PM5430.XXXNLT



- Ⓟ **Height:** 3.1mm Max
- Ⓟ **Footprint:** 4.35mm x 4.35mm Max
- Ⓟ **Current Rating:** up to 6.6Apk
- Ⓟ **Inductance Range:** 3.3uH to 6.8uH
- Ⓟ High current, low DCR, and high efficiency
- Ⓟ High reliability
- Ⓟ Minimized acoustic noise and minimized leakage flux noise
- Ⓟ Available in Commercial (PA5430) and Automotive (PM5430) grades

Electrical Specifications @ 25°C, Operating Temperature Range -55°C to +155°C

Part Number		Inductance 100KHz, 0.1V	Rated ³ Current	DC Resistance	Isat ²	SRF
Commercial	Automotive ⁶	uH±20%	A	mΩ MAX.	A MAX	MHz
PA5430.332NLT	PM5430.332NLT	3.3	6.6	28.6	5.5	43
PA5430.472NLT	PM5430.472NLT	4.7	5.1	44.1	4.5	36
PA5430.682NLT	PM5430.682NLT	6.8	3.9	74.1	3.6	29

Notes:


1. Actual temperature of the component during system operation (ambient plus temperature rise) must be within the standard operating range.
2. The saturation current is the current at which the initial inductance is guaranteed to drop by no more than 40%.
3. The rated current is the DC current required to raise the component temperature by approximately 40 °C. Take note that the components' performance varies depending on the system condition. It is suggested that the component be tested at the system level, to verify the temperature rise of the component during system operation.
4. The part temperature (ambient+temp rise) should not exceed 155 °C under worst case operating conditions. Circuit design, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
5. Parts shown in bold are standard catalog parts and are available through sample stock and distribution. Parts in lighter font are available but are not necessarily held in sample stock or distribution and lead times may be longer. Please contact Pulse for availability.
6. The PM5430.XXXNLT part numbers are AEC-Q200 and IATF16949 certified. The inductance and mechanical dimensions are 100% tested in production but do not necessarily meet a product capability index (Cpk) >1.33 and therefore may not strictly conform to PPAP.
7. Special Characteristics Ⓟ

SMT Power Inductor


High Current Composite Inductor - PA5430.XXXNLT and PM5430.XXXNLT

Mechanical

PA5430/PM5430.XXXNLT and PA5431.XXXNLT



FINAL LAYOUT




SUGGESTED PAD LAYOUT

Series	A	B	C	D	E	F	L	G	H
PA5430/PM5430	4.1±0.25	4.1±0.25	2.8±0.3	3.4±0.3	0.88±0.3	1.6±0.3	3.4 (REF)	1.4 (REF)	3.8 (REF)

All Dimensions in mm.

TAPE & REEL INFO



SURFACE MOUNTING TYPE, REEL/TAPE LIST						
Series	REEL SIZE (mm)		TAPE SIZE (mm)			QTY PCS/REEL
	A	G	P ₁	W	K ₀	
PA5430/PM5430	Ø330	12.4	8	12	3.3	2000

For More Information:

Americas - prodinfo_power@pulseelectronics.com | Europe - power-apps-europe@pulseelectronics.com | Asia - power-apps-asia@pulseelectronics.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2020. Pulse Electronics, Inc. All rights reserved.