



JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS) MINIMUM
BF22180-28B	x = .346 y = .319	1140 @ 0°C	380	5 ± 1	38,000 ±10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
			TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>							
<b>B</b>	RATED LIFE HRS MINIMUM	7/30/09	DRAWN BY	APPVD BY	DATE	SIZE	FSCM NO.	DRAWING NO.	<b>BF22180-28B</b>	
<b>A</b>	CIRCUIT & LAMP VOLTAGE CHANGE	7/19/04	L. WENGSTROM	L.R.	7/30/09	<b>A</b>	<b>55335</b>			
	RELEASED & CANCEL P-0303-14	9/2/03								
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
						NONE	9/2/03	7/30/09	<b>B</b>	1 OF 1