


REV	ECRN	DATE
1	NEW PRODUCTION	20200622



- NOTES:
- 1.ELECTRICAL TEST:100%OPEN,SHORT&MIS WIRE TEST.
 - 2.CONTACT RESISTANCE:24AWG:0.15ohm,28AWG:0.5ohm
 - 3.INSULATOR RESISTANCE:5M ohm.
 - 4.HIGH VOLTAGE:DC 300V 0.01sec.
 - 5.MUST BE ROHS COMPLIANT.

接线表

P1	P2
A4+A9+B4+B9	RED
A7	WHITE
A6	GREEN
A5	DRAIN
A1+A12+B1+B12	BLACK

⑥	I.000001.0400R	TIE	L=100mm COLOR BLACK	1	PCS
⑤	J.000008.0500R	TIN WIRE	TIN WIRE OD:0.8MM	2.5	G
④	C.045P01.0100R	MOLDING	PVC 45P BLACK	13.6	G
③		CONNECTOR	USB2.0 TYPE C/M GOLDDED PLATED SHELL NICKEL PLASTIC: BLACK 56.0KΩ	1	PCS
②		CONNECTOR	USB2.0 TYPE C/M GOLDDED PLATED SHELL NICKEL PLASTIC: BLACK 56.0KΩ	1	PCS
①		CABLE	28AWG(7/0.12TC+250D)*1P+23AWG(37/0.10TC+250D)*2C+D(10/0.10TC)+AL JACKET PVC 60P BLACK OD:2.8±0.1MM L=1000MM±10MM	1	PCS
NO.	PART NO	ITEM	DESCRIPTION	Q'TY	UNIT

RoHS COMPLIANT		东莞市博帆科技有限公司 DongGuan BoFan Electronics Co.,Ltd TEL:076938835098/38835095 FAX:076938835091			
DRAWN BY		比例: FREE	TITLE: USB2.0 TYPE C TO USB2.0 TYPE C		
CHECKED BY		单位: mm	SUPPLIER`S ITEM: 9.00ACCA2904.000R		
APPROVED BY			CUSTOMER:		
			CUSTOMER`S ITEM:		
		DRAWING NO. ACCA-2904	DATE	2020.06.22	