

PM5-M124 SERIES

Smart Sensor Metal Panel Mount Indicators









FEATURES AND BENEFITS

- IP67 rated and RoHS compliant.
- Smart sensor technology automatically senses and adjusts for appropriate light output and intensity. Panel mount indicators are sunlight readable in bright lighting and auto-dimming in dark lighting.
- · Wide viewing angle capabilities with a water clear Fresnel lens (7mm).
- · Solid color indication in green, blue, red, and yellow.
- Black anodized metal housing for ruggedized applications (shock and vibration resistant).
- Fast and easy installation with a panel thickness ranging from 0.040" 0.250" and a standard mounting hole size of 0.315".
- Features non-polarized quick disconnect terminal blades which also work as soldering lugs for wire connection.
- Wide input range (12-24V) suitable for both AC and DC operation.

APPLICATIONS

- Servers and server appliances
- Test and measurement equipment
- Electrical and control instrument panels
- · Military and utility vehicle dashboards
- Commercial and communication control boxes
- · Wireless and power line infrastructure
- · Water and waste treatment equipment

Part Number	Dominant Wave Length (nm)	Emitted Color	Lens Appearance	Voltage	Typical LED Intensity Iv(mcd) @ 0Lx	Viewing Angle
PM5-M124-BLU	465	Blue	Water Clear	12-24 VAC/VDC	20	100°
PM5-M124-GRN	530	Green	Water Clear	12-24 VAC/VDC	20	100°
PM5-M124-RED	625	Red	Water Clear	12-24 VAC/VDC	20	100°
PM5-M124-YLW	590	Yellow	Water Clear	12-24 VAC/VDC	20	100°



SPECIFICATIONS





