

wiSTAR™ Plug-in Switch Module

WIRELESS LIGHTING CONTROLS



wiSTAR™



WIS-PSM

PROJECT INFORMATION

Project Name _____

Catalog No. _____

Date _____

A simple solution for wireless control through any standard outlet. Controlling lamps and electronics in any room is simple when you use Hubbell Controls' *wiSTAR* Plug-In Switch Module.

The module uses radio frequency technology to communicate wirelessly with other *wiSTAR* devices and provide convenient control of lighting and electronic appliances. Simply plug the module into any standard outlet and then plug the lamp or other electronic device into the receptacle on the opposite end. Link the module to a *wiSTAR* switch or occupancy sensor for convenient wireless control.

PRODUCT FEATURES

- Provides switching of plug-in electrical loads
- Communicates with other devices to enable energy savings
- Plugs into any standard outlet, no wiring required
- Easily links with wireless sensors and switches
- Five-year limited warranty
- 120-277 Vac



Device Configuration and Manual Control Buttons with LEDs



HUBBELL
Control Solutions

General Specifications

Power Supply	120VAC, 50/60Hz
Power Consumption	1.1W @ full load, 500mW quiescent
Inputs/Outputs	Standard male plug for power input Standard female plug for controlled output 1 normally open relay Input for accessory tabletop rocker pad Radio Frequency (RF) transceiver 2 Buttons with LEDs for device configuration and manual control
Maximum Load	General Purpose – 15A @ 120VAC Resistive – 15A @ 120VAC Tungsten – 960W @ 120VAC Ballast - 600W @ 120VAC Motor Load Rating - ½ HP @ 120VAC
RF Communications	EnOcean 902 MHz
Transmission Range	80ft. (25m)
Dimensions	4.09" H x 1.85" W x 1.26" D (104mm x 47mm x 32mm)
Cord Lengths	Plug cord: 3ft. (91.4cm) Outlet cord: 1 ft. (30.5cm)
Weight	12.3oz. (348g)
Mounting	Free standing, or mounts to wall using included mounting plate
Environment	Indoor use only 32° to 131° F (0° to 55° C) 5% to 95% relative humidity(non-condensing)
Agency Compliance	Conforms to UL Std. 244A and 1472 Certified to CAN/CSA Std. C22.2 No. 184 FCC: SZV-STM300U IC: 5713A-STM300U
Warranty	Five-year limited
Interoperable Products / EEPs (EnOcean Equipment Profiles)	Product Name (EEP #) Rocker Pad Switch (F6-02-02) Key Card Switch (F6-04-01) Window handle (F6-10-00) 1BS Single Input Contact (D5-00-01) Temperature Sensor, 0° to 40° C (A5-02-05) Occupancy Sensor (A5-07-01) Contact, single input (A5-30-01) Central Gateway (A5-38-08)

Ordering Information

WIS-PSM-WH	
MODEL	
WIS-PSM-WH	wiSTAR™ Plug-In Switch Module, 902MHz, White



HUBBELL
Control Solutions

9601 Dessau Road | Building One | Austin, Texas 78754 | 512-450-1100 | 512-450-1215 fax | www.hubbell-automation.com

4306A 2.4.2016