24 INCHES LENGTH



Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 172204 N-Type Jack Straight Brass White Bronze + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable			Connector B		
Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material Body Finish: IP Rating: Contact Mater Contact Finish Max. Freq.: Booting:	Scription:SMA BHD JK RG174 RG188 RG316 500be:SMAoder:Jackdy Type:Straighttact Type:Solderarity:Standardbedance:50 Ohmunting:Bulkhead - Rear Mountdy Material:Brassdy Finish:GoldRating:Nonentact Material:Beryllium Copperntact Finish:GoldK. Freq.:12.4 GHz		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 24 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	172204 N-Type JK RG174 F N-Type Jack Straight Solder Standard 50 Ohm Cable Brass White Bronze None Phosphor Bronze Gold 11 GHz N-Type Jack Straigh 0°		
		THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED DF ING Part No:	SMA-ST-JK/N-ST-JK G174 24I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	