



# BZX584C2V4-AU SERIES

## SURFACE MOUNT SILICON ZENER DIODES

**VOLTAGE** 2.4 to 75 Volt    **POWER** 200 mWatt



**SOD-523**    Unit : inch(mm)

### FEATURES

- Planar Die construction
- 200mW Power Dissipation
- Zener Voltages from 2.4V~75V
- Ideally Suited for Automated Assembly Processes
- Acquire quality system certificate : TS16949
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

### MECHANICAL DATA

- Case: SOD-523, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Standard packaging: 8mm tape
- Apprx. Weight: 0.00005 ounces, 0.00143 grams



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

| PARAMETER   | SYMBOL | VALUE       | UNITS              |
|---|--------|-------------|--------------------|
| Power Dissipation @ $T_A=25^{\circ}\text{C}$ (Note A) | $P_D$  | 200         | mW                 |
| Operating Junction and Storage Temperature Range      | $T_J$  | -55 to +150 | $^{\circ}\text{C}$ |

### NOTES :

A. Mounted on 100cm<sup>2</sup>(1mm thick) copper areas.



## BZX584C2V4-AU SERIES

| Part Number   | Nominal Zener Voltage            |        |        | Max. Zener Impedance              |     |                                   |      | Max Reverse Leakage Current     |       | Marking Code |
|---------------|----------------------------------|--------|--------|-----------------------------------|-----|-----------------------------------|------|---------------------------------|-------|--------------|
|               | V <sub>Z</sub> @ I <sub>ZT</sub> |        |        | Z <sub>ZT</sub> @ I <sub>ZT</sub> |     | Z <sub>ZK</sub> @ I <sub>ZK</sub> |      | I <sub>R</sub> @ V <sub>R</sub> |       |              |
|               | Nom. V                           | Min. V | Max. V | Ω                                 | mA  | Ω                                 | mA   | μA                              | V     |              |
| BZX584C2V4-AU | 2.4                              | 2.28   | 2.52   | 100                               | 5.0 | 600                               | 1.00 | 50                              | 1.0   | W1           |
| BZX584C2V7-AU | 2.7                              | 2.57   | 2.84   | 100                               | 5.0 | 600                               | 1.00 | 20                              | 1.0   | W2           |
| BZX584C3-AU   | 3                                | 2.85   | 3.15   | 95                                | 5.0 | 600                               | 1.00 | 10                              | 1.0   | W3           |
| BZX584C3V3-AU | 3.3                              | 3.14   | 3.47   | 95                                | 5.0 | 600                               | 1.00 | 5.0                             | 1.0   | W4           |
| BZX584C3V6-AU | 3.6                              | 3.42   | 3.78   | 90                                | 5.0 | 600                               | 1.00 | 5.0                             | 1.0   | W5           |
| BZX584C3V9-AU | 3.9                              | 3.71   | 4.10   | 90                                | 5.0 | 600                               | 1.00 | 3.0                             | 1.0   | W6           |
| BZX584C4V3-AU | 4.3                              | 4.09   | 4.52   | 90                                | 5.0 | 600                               | 1.00 | 3.0                             | 1.0   | W7           |
| BZX584C4V7-AU | 4.7                              | 4.47   | 4.94   | 80                                | 5.0 | 500                               | 1.00 | 3.0                             | 2.0   | W8           |
| BZX584C5V1-AU | 5.1                              | 4.85   | 5.36   | 60                                | 5.0 | 480                               | 1.00 | 2.0                             | 2.0   | W9           |
| BZX584C5V6-AU | 5.6                              | 5.32   | 5.88   | 40                                | 5.0 | 400                               | 1.00 | 1.0                             | 2.0   | WA           |
| BZX584C6V2-AU | 6.2                              | 5.89   | 6.51   | 10                                | 5.0 | 150                               | 1.00 | 3.0                             | 4.0   | WB           |
| BZX584C6V8-AU | 6.8                              | 6.46   | 7.14   | 15                                | 5.0 | 80                                | 1.00 | 2.0                             | 4.0   | WC           |
| BZX584C7V5-AU | 7.5                              | 7.13   | 7.88   | 15                                | 5.0 | 80                                | 1.00 | 1.0                             | 5.0   | WD           |
| BZX584C8V2-AU | 8.2                              | 7.79   | 8.61   | 15                                | 5.0 | 80                                | 1.00 | 0.7                             | 5.0   | WE           |
| BZX584C8V7-AU | 8.7                              | 8.27   | 9.14   | 15                                | 5.0 | 100                               | 1.00 | 0.7                             | 5.0   | 3C           |
| BZX584C9V1-AU | 9.1                              | 8.65   | 9.56   | 15                                | 5.0 | 100                               | 1.00 | 0.5                             | 6.0   | WF           |
| BZX584C10-AU  | 10                               | 9.50   | 10.50  | 20                                | 5.0 | 150                               | 1.00 | 0.2                             | 7.0   | WG           |
| BZX584C11-AU  | 11                               | 10.45  | 11.55  | 20                                | 5.0 | 150                               | 1.00 | 0.1                             | 8.0   | WH           |
| BZX584C12-AU  | 12                               | 11.40  | 12.60  | 25                                | 5.0 | 150                               | 1.00 | 0.1                             | 8.0   | WI           |
| BZX584C13-AU  | 13                               | 12.35  | 13.65  | 30                                | 5.0 | 170                               | 1.00 | 0.1                             | 8.0   | WK           |
| BZX584C14-AU  | 14                               | 13.30  | 14.70  | 30                                | 5.0 | 170                               | 1.00 | 0.1                             | 10.00 | WJ           |
| BZX584C15-AU  | 15                               | 14.25  | 15.75  | 30                                | 5.0 | 200                               | 1.00 | 0.1                             | 10.50 | WL           |
| BZX584C16-AU  | 16                               | 15.20  | 16.80  | 40                                | 5.0 | 200                               | 1.00 | 0.1                             | 11.20 | WM           |
| BZX584C17-AU  | 17                               | 16.15  | 17.85  | 40                                | 5.0 | 200                               | 1.00 | 0.1                             | 12.20 | 4C           |
| BZX584C18-AU  | 18                               | 17.10  | 18.90  | 45                                | 5.0 | 225                               | 1.00 | 0.1                             | 12.60 | WN           |
| BZX584C20-AU  | 20                               | 19.00  | 21.00  | 55                                | 5.0 | 225                               | 1.00 | 0.1                             | 14.00 | WO           |
| BZX584C22-AU  | 22                               | 20.90  | 23.10  | 55                                | 5.0 | 250                               | 1.00 | 0.1                             | 15.40 | WP           |
| BZX584C24-AU  | 24                               | 22.80  | 25.20  | 70                                | 5.0 | 250                               | 1.00 | 0.1                             | 16.80 | WR           |
| BZX584C27-AU  | 27                               | 25.65  | 28.35  | 80                                | 5.0 | 300                               | 1.00 | 0.1                             | 18.90 | WS           |
| BZX584C28-AU  | 28                               | 26.60  | 29.40  | 80                                | 5.0 | 300                               | 1.00 | 0.1                             | 20.50 | 5C           |
| BZX584C30-AU  | 30                               | 28.50  | 31.50  | 80                                | 5.0 | 300                               | 1.00 | 0.1                             | 21.00 | WT           |
| BZX584C33-AU  | 33                               | 31.35  | 34.65  | 80                                | 5.0 | 325                               | 1.00 | 0.1                             | 23.10 | WU           |
| BZX584C36-AU  | 36                               | 34.20  | 37.80  | 90                                | 5.0 | 350                               | 1.00 | 0.1                             | 25.20 | WW           |
| BZX584C39-AU  | 39                               | 37.05  | 40.95  | 130                               | 5.0 | 350                               | 1.00 | 0.1                             | 27.30 | WX           |
| BZX584C43-AU  | 43                               | 40.85  | 45.15  | 150                               | 5.0 | 375                               | 1.00 | 0.1                             | 30.10 | WY           |
| BZX584C47-AU  | 47                               | 44.65  | 49.35  | 170                               | 5.0 | 375                               | 1.00 | 0.1                             | 32.90 | WZ           |
| BZX584C51-AU  | 51                               | 48.45  | 53.55  | 100                               | 5.0 | 400                               | 1.00 | 0.1                             | 38.00 | XA           |
| BZX584C56-AU  | 56                               | 53.20  | 58.80  | 135                               | 2.5 | 1000                              | 1.00 | 0.1                             | 42.00 | X2           |
| BZX584C62-AU  | 62                               | 58.90  | 65.10  | 150                               | 2.5 | 1000                              | 1.00 | 0.1                             | 46.00 | X3           |
| BZX584C68-AU  | 68                               | 64.60  | 71.40  | 200                               | 2.5 | 1000                              | 1.00 | 0.1                             | 51.00 | X4           |
| BZX584C75-AU  | 75                               | 71.25  | 78.75  | 250                               | 2.5 | 1000                              | 1.00 | 0.1                             | 56.00 | X5           |



# BZX584C2V4-AU SERIES




Fig. 1 STEADY STATE POWER DERATING




Fig. 2 TEMPERATURE COEFFICIENTS




Fig. 3 TYPICAL LEAKAGE CURRENT




Fig. 4 TYPICAL FORWARD VOLTAGE




# BZX584C2V4-AU SERIES

## MOUNTING PAD LAYOUT

SOD-523

Unit : inch(mm)



## ORDER INFORMATION

- Packing information  
T/R - 12K per 13" plastic Reel  
T/R - 5K per 7" plastic Reel



# BZX584C2V4-AU SERIES

## Part No\_packing code\_Version

BZX584C2V4-AU\_R1\_000A1

BZX584C2V4-AU\_R2\_000A1

For example :

**RB500V-40** **R2** **00001**



| Packing Code <b>XX</b>               |                      |                                  |                      | Version Code <b>XXXXX</b> |                      |                                       |
|--------------------------------------|----------------------|----------------------------------|----------------------|---------------------------|----------------------|---------------------------------------|
| Packing type                         | 1 <sup>st</sup> Code | Packing size code                | 2 <sup>nd</sup> Code | HF or RoHS                | 1 <sup>st</sup> Code | 2 <sup>nd</sup> ~5 <sup>th</sup> Code |
| Tape and Ammunition Box (T/B)        | <b>A</b>             | N/A                              | <b>0</b>             | <b>HF</b>                 | <b>0</b>             | serial number                         |
| Tape and Reel (T/R)                  | <b>R</b>             | 7"                               | <b>1</b>             | <b>RoHS</b>               | <b>1</b>             | serial number                         |
| Bulk Packing (B/P)                   | <b>B</b>             | 13"                              | <b>2</b>             |                           |                      |                                       |
| Tube Packing (T/P)                   | <b>T</b>             | 26mm                             | <b>X</b>             |                           |                      |                                       |
| Tape and Reel (Right Oriented) (TRR) | <b>S</b>             | 52mm                             | <b>Y</b>             |                           |                      |                                       |
| Tape and Reel (Left Oriented) (TRL)  | <b>L</b>             | PANASERT T/B CATHODE UP (PBCU)   | <b>U</b>             |                           |                      |                                       |
| FORMING                              | <b>F</b>             | PANASERT T/B CATHODE DOWN (PBCD) | <b>D</b>             |                           |                      |                                       |



## BZX584C2V4-AU SERIES

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.