

SPECIFICATION CONTROL DRAWING			7528A1424
<b>CHEMINAX</b>	75 OHM, AWG 28, 7 STRANDS OF AWG 36, COAXIAL CABLE	Date	12-5-13
		Revision	A
THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.			
CONSTRUCTION DETAILS		ELECTRICAL CHARACTERISTICS	
DIMENSIONS ARE NOMINAL VALUES IN INCHES, UNLESS OTHERWISE DESIGNATED.  		CHARACTERISTIC IMPEDANCE      75 ± 5 ohms, Method A CAPACITANCE                        17.6 pF/ft. (nominal) VELOCITY OF PROPAGATION      77% (nominal)	
		ADDITIONAL REQUIREMENTS	
		<u>ELECTRICAL</u>	
		CONDUCTOR RESISTANCE	74.0 ohms/1000 ft. (nominal)
		INSULATION RESISTANCE	10,000 megohms (minimum) for 1000 ft.
		JACKET FLAWS	
		SPARK TEST	1.0 kV (rms)
		IMPULSE TEST	6.0 kV (peak)
		VOLTAGE WITHSTAND (DIELECTRIC)	1500 volts (rms)
		<u>ENVIRONMENTAL</u>	
		FLAMMABILITY	Method B
		HEAT SHOCK	225°C
		LOW TEMPERATURE-COLD BEND	-55°C/2.75 inch mandrel
		VOLTAGE WITHSTAND (Post Environmental)	1000 volts (rms), 1 minute
		<u>PHYSICAL</u>	
		INSULATION (DIELECTRIC)	
		ELONGATION	50% (minimum)
		TENSILE STRENGTH	600 lbf/in <sup>2</sup> (minimum)
		JACKET	
		ELONGATION	200% (minimum)
		TENSILE STRENGTH	2000 lbf/in <sup>2</sup> (minimum)
		JACKET THICKNESS	.010 inch (nominal)
		SHIELD COVERAGE	90% (minimum)
		WEIGHT	8.3 lbs/1000 ft. (nominal)
		<u>ENGINEERING REFERENCE</u>	
		MAX TEMPERATURE RATING	150°C continuous conductor temperature
Outer jacket color will be translucent white (designated by a "-9X" appended to the part number, e.g. 7528A1424-9X), unless otherwise specified.			
Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.			
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
Page 1 of 1	Rayfoam, Cheminax, Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.		



Raychem Wire & Cable  
 501 Oaks Avenue  
 Redwood City, California 94063-3800  
 Ph. 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.