



- .035 DIA HOLE IS RECOMMENDED FOR .125 MAX THICK P.C. BOARD.
 - CONNECTOR MATES WITH ANY AMP 78 POSN PLUG.
 - POST TIPS WILL FALL WITHIN &&D .020 TRUE POSITION OF EACH OTHER.
- 4 UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
 5 FINISH: CADMIUM PER QQ-416.
 6 FINISH: ZINC PLATED PER ASTM-B-633 .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+).

REMARKS	- 6	.375 MAX	.275±.025	5-211596-1
	NOT RELEASED FOR PRODUCTION 5	.275 MAX	.375±.025	211596-2
	-	.375 MAX	.275±.025	211596-1
		DIM B	DIM A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C.C.THOMAS 8-11-97	Tyco Electronics Corporation	
DIMENSIONS: INCHES		CHK H.WYNKOOP 11-24-97	Harrisburg, PA 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	NAME	
0 PLC	± -	PRODUCT SPEC		
1 PLC	± -	APPLICATION SPEC		
2 PLC	± -	SIZE		
3 PLC	± .005	CAGE CODE		
4 PLC	± -	DRAWING NO		
ANGLES	± -	RESTRICTED TO		
MATERIAL SEE CALLOUTS	FINISH SEE CALLOUTS	WEIGHT	A1 00779 ©=211596	
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 OF 1	REV J