



**GAIG**  
LABORATORIES, INC.



## DeoxIT® Shield S5L Liquid, S-Series Contact & Connector Protector

### 1. Part No.:

- S5L-25CA (25 mL squeeze bottle)
- S5L-4A (118 mL, coated bottle)
- S5L-32A (944 mL, container)
- S5L-55GA (55 gal., drum)

### 2. Product Description:

Contact lubricant and protectant for metal surfaces.  
Oxidation and corrosion deterrent.  
Improves conductivity, maintains optimum signal quality.  
DeoxIT® Shield also reduces wear and abrasion, arcing, RFI and intermittent connections and improves connector performance/reliability.  
Ideal for severe environments. On oxidized surfaces, pre-treat with DeoxIT® D-Series contact cleaner.  
Temperature range: -34°C to +210°C.



### 3. Features/Benefits:

*5% Liquid, Usually for Production Applications, Flushing Action, Prevents Over Application of DeoxIT®, Safe on most Plastics.*

DeoxIT® Shield S100L concentrate has 0.0% chemical cleaning action.  
Ideal for severe environments (humidity, salts, pollutants, sulfur, etc.)  
Excellent protection, good conductivity enhancing, excellent lubrication.  
Creates a long lasting barrier against oxidation and corrosion.  
No ozone depletion.  
Reduces intermittent connections, arcing, RFI, wear and abrasion.  
**Cleaner Audio - Clearer Video - Reliable Data.**

### 4. Formulation:

- 5% DeoxIT® Shield S100L
- 20% 1,1,1,3,3-PENTAFLUOROPROPANE (460-73-1)
- 75% odorless mineral spirits (64742-88-7)

**VOC COMPLIANT** **ROHS COMPLIANT**

### 5. Which DeoxIT® product do I Use:

- ▶ Use **DeoxIT® D-Series** contact cleaner on surfaces that have been in service or have visual signs of oxidation. Contains 20% active cleaner.
- ▶ Use **DeoxIT® Gold G-Series** conditioner on new surfaces, and gold plated surfaces. Ideal for preventing dendrite/fretting corrosion. Protects both surface and base metals. Ideal for critical applications. Contains >1% active cleaner.
- ▶ Use **DeoxIT® Shield S-Series** to protect surfaces from severe environments (humidity, salts, pollutants, sulfur, etc.). Use on clean surface. Contains 0% active cleaner.



Home of the DeoxIT® family of  
Environmentally-Safer Contact Cleaners and  
Connector Enhancing Treatments  
Made in USA



Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

## 6. Directions for Use:

1. Turn off, unplug the device.
2. On surfaces that have been in service or have visual signs of oxidation or corrosion pre-treat with DeoxIT® D-Series contact cleaner or other cleaning process (ultra-sonics). Components, contacts and connectors may appear to be clean; however, they may have slight oxidation on the surfaces. When in doubt, first clean with DeoxIT® D-Series. You do not want apply DeoxIT® Shield S-Series over dirty/oxidized metal surfaces.
3. Apply DeoxIT® Shield S-Series contact protector to contact/connector metal surfaces.
4. Operate the part/device to help distribute the DeoxIT® Shield. Apply one more short burst. Wait two minutes before turning on equipment. Test for compatibility before use.
5. **For extended protection:** For **severe environments** (humidity, salts, pollutants, sulfur, outdoor applications, etc.) and to apply an additional environmental barrier, apply one of the DeoxIT® Greases. See Data Sheets DS-L260 and DS-M260 for additional information;  
Link: <http://store.caig.com/s.nl/sc.2/category.185/f>
6. For production applications, contact a CAIG representative for information and/or recommendations.

## 7. Other Applicators:

Part No.	% DeoxIT®	VOC (%)	Applicator	Size	Flammable/Nonflammable
S5S-6	5%	75%	spray	163 g	flammable
SN5S-6N	5%	0%	spray	163 g	nonflammable
SN5S-2N	5%	0%	mini-spray	40 g	nonflammable
S100S-2	100%	0%	spray	57g	nonflammable
S100P	100%	0%	pen	6 mL	nonflammable
S100L-P6C	100%	0%	oiler pen	6 mL	nonflammable
S50W	100%	0%	wipes	50 count	nonflammable
S1W	100%	0%	wipes	individual	nonflammable
S100L-2C	100%	0%	tube	2 mL	nonflammable
S100L-2DB	100%	0%	brush bottle	7.4 mL	nonflammable
S100L-25C	100%	0%	needle dispenser	25 mL	nonflammable
S100L (bulk, many sizes)	100%	0%	bottle/drum	assort.	nonflammable

## 8. Product Selection Guides:

### DeoxIT® - Product Selection Guide

	DeoxIT®	DeoxIT® GOLD	DeoxIT® GOLD GxL	DeoxIT® GOLD Gx2	DeoxIT® SHIELD	DeoxIT® FaderLube
New Surfaces		✓	✓	✓	✓	✓
* In Service / Used	✓					✓
Gold surfaces		✓	✓	✓		
Oxidation / corrosion visible	✓					
Conductive plastics						✓
** Outdoor / Severe environments	✓					✓
Deoxidizing / cleaning properties	20%	0.1%	0.1%	0.0%	0.0%	0.0%
Metal / Plastic surfaces	Yes	Yes	Yes	Yes	Yes	
Plastics compatibility	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent
Temperature range (°C)	-34/200	-45/240	-45/310	-45/500	-34/210	-26/150
Stationary & moving surfaces	Yes	Yes	Yes	Yes	Yes	Yes
Seals & protects base metals	Good	Excellent	Excellent	Excellent	Good	No

✓ All products are Nonflammable and RoHs Compliant

\* In Service: Clean with DeoxIT®. For added protection, follow with DeoxIT® GOLD (indoors), DeoxIT® SHIELD (outdoors) or DeoxIT® Grease (additional barrier).

\*\* Severe environments: Pre-clean with DeoxIT®. Follow with DeoxIT® SHIELD or DeoxIT® Grease.

### DeoxIT® - Spray Selection Guide

Product Series	FP	QD	NF	PC	VOC
Standard - 5% solution	✓			✓	75% (588g/L)
D5S-6, D5MS-15, G5S-6, G5MS-15, S5S-6, S5MS-15, F5S-6, F5MS-15					
N Series - 5% solution		✓	✓	✓	0.0%
DN5S-6N, DN5S-2N, GN5S-6N, GN5S-2N, SN5S-6N, SN5S-2N					
X Series - 5% solution		✓	✓	✓	0.0%
GX5S-6N					
100% Spray solution			✓	✓	0.0%
D100S-2, G100S-2, F100S-L2					

FP = Flushing properties QD = Quick dry / non drip

NF = Nonflammable PC = Plastics compatibility VOC = VOC (%)



Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

### 9. Materials Compatibility (Plastics, Rubber, Elastomeric and Metals):

(Rating: Not compatible, Poor, Fair, Good, Excellent), (N/A = Not applicable (no solvents and propellants))

(\* If the product is not 100% DeoxIT® then the package is rated before and after the solvents/propellants are applied to materials. Compatibility testing is always recommended)

Material Name	Rating (*100% DeoxIT®)	Rating (*with solvents)
ABS	Excellent	Fair-Good
Nylon	Excellent	Excellent
Lexan	Excellent	Excellent
HDPE	Good	Good
LDPE	Good	Good
C.E.Phenolic	Excellent	Good
Epoxy	Excellent	Excellent
Polycarbonate	Excellent	Fair-Good
PMMA	Fair	Poor
POM	Excellent	Excellent
PP	Excellent	Good
PS	Fair	Fair
PTFE	Excellent	Excellent
PVC	Excellent	Excellent
TPE/Rubber/Varnish	Poor	Poor

#### IMPORTANT:

**Rating, 100% DeoxIT®:** Any of the above that fall into the “Fair” and “Poor” categories should be thoroughly tested for compatibility. They may be compatible, however, it will depend on the manufacturing process of the materials. Acrylics, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use. On porous materials; i.e. wood, rubber, cloth, some phenolics, semi-cured materials, no liquid or solvents should be used. Occasionally, DeoxIT® will get onto unwanted surfaces, quickly wipe off surface and usually no damage will occur.

**Rating, with solvents:** Similar to rating above (100% DeoxIT®). However, any rating worse than the 100% DeoxIT® may require additional care. If DeoxIT is applied to unwanted areas or materials, wipe off surface quickly and usually no damage will occur. Alternatively, apply DeoxIT® onto a lint-free swab or cloth first and then wipe onto desired metal surface.

### 10. DeoxIT® Essential Reference:

**DeoxIT® D-Series** - Brings old systems back to life!

**DeoxIT® Gold G-Series** - Maintains new system performance!

**DeoxIT® Shield S-Series** - Maintains new system performance for severe environments!

**DeoxIT® Fader F-Series** - Clean, lubricate & protect conductive plastic and carbon compound faders!





Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

### 11. Shipping and Additional Information:

Hazardous: ORMD  
VOC (%): Part No. S5L-A, 75% (588 g/L)

### 12. Other Information:

RoHS Compliant: YES  
VOC Compliant: YES  
**MSDS Link, S5L** <http://caig.com/material-safety-data-sheets/>  
DeoxIT® Product Sheet: <http://caig.com/technical-data/>  
CAIG Essential Guide: <http://caig.com/product-literature/#toggle-id-1>  
WHY DeoxIT® is Different: <http://caig.com/product-literature/#toggle-id-8>

### 13. MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither CAIG Laboratories, Inc., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. All service performed on internal parts and equipment should be provided by qualified technicians.

### 14. Contact Information:



Website: [www.caig.com](http://www.caig.com)  
[www.deoxit.com](http://www.deoxit.com)

General email: [info@caig.com](mailto:info@caig.com)

Technical email: [tech@caig.com](mailto:tech@caig.com)

#### North America (Headquarters):

**CAIG Laboratories, Inc.**  
12200 Thatcher Court  
Poway, CA 92064 USA  
Tel: (858) 486-8388  
Fax: (858) 486-8398

#### Distributors (Domestic & International):

<http://caig.com/distributors/>



#### CAIG Laboratories, Inc.

12200 Thatcher Court, Poway, CA 92064 U.S.A.  
P: 858/486-8388 | E: [info@caig.com](mailto:info@caig.com)  
WEB: [www.caig.com](http://www.caig.com) | [www.deoxit.com](http://www.deoxit.com)

