

Product: <u>5300UP</u> ☑

Audio Cable, 2 Conductor 18 AWG, BC, Unshielded, CM




Product Description

Commercial Audio Cable, Rated-CM, 2-18 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

Technical Specifications

Construction Details



Temperature

| UL Temperature | Operating | | |
|----------------|----------------|--|--|
| 75°C | -20°C To +75°C | | |

Bend Radius

| Stationary Min. | Installation Min | |
|-------------------|------------------|---|
| 1.84 in (46.7 mm) | 1.84 in | 1 |
| Max. Pull Tension | | 4 |
| Bulk Cable Weight | t: | 1 |

Standards and Compliance

| Environmental Suitability: | Indoor (Not Riser or Plenum), Indoor |
|----------------------------------|--|
| Flammability / Reaction to Fire: | UL1685 UL Loading |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 800, CM |
| CEC / C(UL) Compliance: | СМ |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

History

| Update and Revision: Revision Number: 0.427 Revision Date: 12-19-2022 | |
|---|--|
|---|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|-----------------|-------------|--------------|----------|--------------|----------|
| 5300UP 0101000 | Black | Reel | 1,000 ft | 612825421573 | С |
| 5300UP 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825159322 | |
| 5300UP D15500 | Blue | Reel | 500 ft | 612825159315 | |
| 5300UP D151000 | Blue | Reel | 1,000 ft | 612825159339 | |
| 5300UP D15U1000 | Blue | UnReel | 1,000 ft | 612825336822 | |
| 5300UP 0081000 | Gray | Reel | 1,000 ft | 612825421566 | |
| 5300UP 008Z1000 | Gray | ReelTuff Box | 1,000 ft | 612825159391 | |
| 5300UP 005U500 | Green, Dark | UnReel | 500 ft | 612825159377 | |
| 5300UP 0051000 | Green, Dark | Reel | 1,000 ft | 612825159346 | |
| 5300UP 005U1000 | Green, Dark | UnReel | 1,000 ft | 612825159353 | |
| 5300UP 009500 | White | Reel | 500 ft | 612825159384 | |
| 5300UP 009U1000 | White | UnReel | 1,000 ft | 612825159407 | |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.