

Catalog Number
Project Number
Type

DESCRIPTION

LED-GIMBAL-PRO Series lights are bright, energy efficient and elegantly designed. They are an ideal solution for commercial and residential applications requiring compact shape, superior quality and visual aesthetics. This 8W light produces 696-784Lm (depending on the CCT). At 1.77" tall and 2.48" round they can fit into tight spaces that a traditional recessed can light can't, such as ceilings with ductwork/piping/obstructions, hot-roof ceilings with limited vertical clearance, and tight soffits. It comes in Black, White and Brushed Nickel Finishes. Each light can be set at 3000K, 4000K or 5000K CCT (Adjustable). These lights feature an easily adjustable LED face (Gimbal) that can be pointed straight downward, making them compatible with sloped ceilings.

Lifespan: 39,000 hrs

Certifications: ETL, CE, RoHS

Warranty: 5 years

ELECTRICAL

Lumen output: 696-784 lm

Wattage: 8 watts

CCT (adjustable): 3000K, 4000K, 5000K

Operating voltage: 110-130 VAC

Dimming: Dimmable

MATERIAL / OPTICS

Finish: White, black, brushed nickel

Interchangeable trim ring

Light direction: Downlight

Beam angle: 40 degrees

4" RECESSED DIMMABLE ADJUSTABLE CCT LIGHT RCTG-7W-4IN



Diameter	Height
Module - 2.48 in (63 mm)	1.77 in (45 mm)
Trim - 4.72 in (120 mm)	
Cutout (min) - 2.75 in (70 mm)	
Cutout (max) - 2.88 in (73 mm)	

Example: **RCTG-7W-4IN-WH**

Model	Power	Voltage	Trim Size	Finish
RCTG	7W 696-784 lm	110-130 VAC	4IN	WH White
				B Black
				N Brushed Nickel

TRIM OPTIONS



BRUSHED NICKEL



BLACK



WHITE

RECESSED LIGHT AND DRIVER



PHOTOMETRICS

