



IMZ1AS-AU

Complementary Dual General Purpose Transistor

Voltage

50V /
-50V

Current

0.15 /
-0.15A

Features



- Silicon PNP/NPN epitaxial type
- Tr1: PNP
Tr2: NPN
- Ideal for Low Power Amplification and Switching
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: SOT-23 6L Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0005 ounces, 0.014 grams
- Marking: 1AS

SOT-23 6L

Unit: inch(mm)



Pin Assignment

1. Tr1 (PNP) Emitter
2. Tr1 (PNP) Base
3. Tr2 (NPN) Collector
4. Tr2 (NPN) Emitter
5. Tr2 (NPN) Base
6. Tr1 (PNP) Collector

Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	Tr1	Tr2	UNITS
Collector-Base Voltage	V_{CBO}	50	-50	V
Collector-Emitter Voltage	V_{CEO}	60	-60	
Emitter-Base Voltage	V_{EBO}	7	-6	
Collector Current (DC)	I_C	150	-150	mA
Total Power Dissipation	P_D	300		mW
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~150		$^\circ\text{C}$
Typical Thermal Resistance from Junction to Ambient ^(Note)	$R_{\theta JA}$	100		$^\circ\text{C/W}$

Note: Mounted on FR4 with 2oz. PCB at 1 inch square copper pad.



IMZ1AS-AU

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Tr1 (PNP)						
OFF Characteristics						
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C = -1\text{mA}, I_B = 0\text{A}$	-50	-	-	V
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C = -50\mu\text{A}, I_E = 0\text{A}$	-60	-	-	
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E = -50\mu\text{A}, I_C = 0\text{A}$	-6	-	-	
Collector-Base Cutoff Current	I_{CBO}	$V_{CB} = -60\text{V}, I_E = 0\text{A}$	-	-	-100	nA
Emitter-Base Cutoff Current	I_{EBO}	$V_{EB} = -6\text{V}$	-	-	-100	
ON characteristics						
DC Current Gain	h_{FE}	$V_{CE} = -6\text{V}, I_C = -1\text{mA}$	120	-	560	-
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = -50\text{mA}, I_B = -5\text{mA}$	-	-150	-500	mV
Transition Frequency	f_T	$I_E = -2\text{mA}, V_{CE} = -12\text{V}$ $f = 100\text{MHz}$	-	140	-	MHz
Collector Output Capacitance	C_{OB}	$V_{CB} = -12\text{V}, I_E = 0\text{A},$ $f = 100\text{MHz}$	-	4	5	pF
Tr2 (NPN)						
OFF Characteristics						
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C = 1\text{mA}, I_B = 0\text{A}$	50	-	-	V
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C = 50\mu\text{A}, I_E = 0\text{A}$	60	-	-	
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E = 50\mu\text{A}, I_C = 0\text{A}$	7	-	-	
Collector-Base Cutoff Current	I_{CBO}	$V_{CB} = 60\text{V}, I_E = 0\text{A}$	-	-	100	nA
Emitter-Base Cutoff Current	I_{EBO}	$V_{EB} = 7\text{V}$	-	-	100	
ON characteristics						
DC Current Gain	h_{FE}	$V_{CE} = 6\text{V}, I_C = 1\text{mA}$	120	-	560	-
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = 50\text{mA}, I_B = 5\text{mA}$	-	100	400	mV
Transition Frequency	f_T	$I_E = 2\text{mA}, V_{CE} = 12\text{V}$ $f = 100\text{MHz}$	-	180	-	MHz
Collector Output Capacitance	C_{OB}	$V_{CB} = 12\text{V}, I_E = 0\text{A},$ $f = 100\text{MHz}$	-	2	3.5	pF

Note: 1. Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$



IMZ1AS-AU

TYPICAL CHARACTERISTIC CURVES




Fig.1 DC Current Gain

Tr1 (PNP)




Fig.2 Collector Current




Fig.3 Collector-Emitter Saturation Voltage




Fig.4 Base-Emitter Saturation Voltage




Fig.5 Base-Emitter Voltage



IMZ1AS-AU

TYPICAL CHARACTERISTIC CURVES




Fig.6 DC Current Gain

Tr2 (NPN)




Fig.7 Collector Current




Fig.8 Collector-Emitter Saturation Voltage




Fig.9 Base-Emitter Saturation Voltage




Fig.10 Base-Emitter Voltage




IMZ1AS-AU

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
IMZ1AS-AU_S1_000A1	SOT-23 6L	3K pcs / 7" reel	1AS	Halogen free

Mounting Pad Layout





IMZ1AS-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.