



**ENVIRONMENTAL SPECIFICATION**

Item	Specification
Temperature	Operation: 0°C ~ 70°C Storage: -40°C ~ 85°C Junction temperature: max. 90°C for 5 minutes
Bending	10N
Torque	+/- 2.5 degree
Drop test	1.5m free fall

**PHYSICAL MECHANICAL OUTLINE:**

Dimensions Card Package	11mmx15mm Min. 10.9mmx14.9mm Max.11.1mmx15.1mm
Thickness	1.0mm +/- 0.1mm
Surface	Plain (except contact area)
Edges	Smooth edges
Inverse insertion	Protection on right corner (top view)

**ORDERING INFORMATION**

Speed	Capacity	P/N
Class4	4GB	AP4GMCSH4-X
	8GB	AP8GMCSH4-X
	16GB	AP16GMCSH4-X
	32GB	AP32GMCSH4-X

**Global Offices**

**Taiwan (HQ)**

**Apacer Technology Inc.**  
1F., No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City 236, Taiwan R.O.C.  
Tel: 886-2-2267-8000  
Fax: 886-2-2267-2261  
[amtsales@apacer.com](mailto:amtsales@apacer.com)

**U.S.A**

**Apacer Memory America, Inc.**  
386 Fairview Way, Suite102, Milpitas, CA 95035  
Tel: 1-408-518-8699  
Fax: 1-408-935-9611  
[sa@apacerus.com](mailto:sa@apacerus.com)

**Japan**

**Apacer Technology Corp.**  
5F, Matsura Bldg., Shiba, Minato-Ku Tokyo, 105-0014, Japan  
Tel: 81-3-5419-2668  
Fax: 81-3-5419-0018  
[jpserives@apacer.com](mailto:jpserives@apacer.com)

**Europe**

**Apacer Technology B.V.**  
Science Park Eindhoven 5051 5692 EB Son, The Netherlands  
Tel: 31-40-267-0000  
Fax: 31-40-267-0000#6199  
[sale@apacer.nl](mailto:sale@apacer.nl)

**China**

**Apacer Electronic (Shanghai) Co., Ltd**  
1301, No.251,Xiaomujiao Road, Shanghai, 200032, China  
Tel: 86-21-5529-0222  
Fax: 86-21-5206-6939  
[sales@apacer.com.cn](mailto:sales@apacer.com.cn)

**India**

**Apacer Technologies Pvt Ltd,**  
# 535, 1st Floor, 8th cross, JP Nagar 3rd Phase, Bangalore – 560078, India  
Tel: 91-80-4152-9061  
[Sales\\_india@apacer.com](mailto:Sales_india@apacer.com)