18 INCHES LENGTH



Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 000-69475 BNC Plug Straight Brass Nickel

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

		Connector A	A		Cable		Connector B		
Pa	art #:	112234		Part #:	RG-174	Part #:	000-69475		
De	escription:	BNC Clamp BHD		Dielectric: F Shielding: E Diameter: 0 Impedance: 5	RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None	Description:	BNC Clamp PLUG RG188 500 BNC Plug		
₍ T	ype:	BNC				Туре:			
G	ender:	Jack				Gender:			
B	ody Type:	Straight				Body Type:	Straight		
C	ontact Type:	Crimp				Contact Type:	Solder		
Po	olarity:	Standard				Polarity:	Standard		
Im	npedance:	50 Ohm		Testing:	Continuity Hi-Pot	Impedance:	50 Ohm Cable Brass Nickel None Brass Silver 4 GHz		
M	lounting:	Bulkhead - Rear I		Length:	18 Inches	Mounting:			
B	ody Material:	Brass				Body Material:			
B	ody Finish:	Nickel				Body Finish:			
IP	PRating:	None				IP Rating:			
C	ontact Material:	Beryllium Copper		ID		Contact Material:			
C	ontact Finish:	Silver	nt BHD			Contact Finish:			
M	lax. Freq.:	4 GHz				Max. Freq.:			
В	ooting:	BNC Jack Straigh				Booting:	BNC Plug Straight		
						Clocking:	0°		
Amphenol FOR ANY PURPOSE DETRININC. IT MAY NOT BE REPRO			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU	AND MUST NOT BE U TAL TO CUSTOM CAI CED OR TRANSCRIBI	BLE ED	Title: BNC-ST-JK/BNC-ST-PL G174 18I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY:	
CONTROLLED DOCUMENT - DO NOT COPY			IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		NG Part No:				