

DIMENSIONING AND TOLERANCING PER ASME Y14.5M (ISO STANDARDS). THIS DRAWING IS A CONTROLLED DOCUMENT.

TOOL NUMBER	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	INSUL. ADJ.	FLIP LOCATOR	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS ¹		CONTACT DESCRIPTION	APPLIC. SPECIF.
							LOOSE PIECE	STRIP FORM		
91563-1 91563-3	0.20-0.56 [24-20]	1.50-2.20 [.059-.087]	YES	NO	4.0-4.5 [.157-.177]	0.98 ± 0.05 [.039 ± .002]	171699-[] ⁴	171630-[] ^{3 4}	ECONOSEAL "J" II, .070 Series Contacts	114-5082
	0.20-0.56 [24-20]				1.02 ± 0.05 [.040 ± .002]	173600-[] ⁴	171631-[] ^{3 4}			
91573-1 91573-3	0.50-0.89 [20-18]	2.00-2.60 [.079-.102]	NO	NO	3.5-4.5 [.138-.177]	1.20-1.35 [.047-.053]	175027-[] 175030-[]	173631-[] ³ 173645-[] ³	.070 Series Contacts	114-5091 114-5092 114-5091-9 114-5092-9
	1.25-1.42 [16]				1.45-1.60 [.057-.063]					
91580-1 91580-3	0.20-0.22 [24]	1.20-1.50 [.047-.059]	NO	NO	3.5-4.5 [.138-.177]	1.00-1.10 [.039-.043]	175026-[] 175029-[]	173630-[] ³ 173633-[] ³	.070 Series Contacts	114-5091-9 114-5092-9
	0.30-0.35 [22]	1.20-1.60 [.047-.063]				1.05-1.18 [.041-.046]				
91583-1 91583-3	0.50-0.89 [20-18]	2.00-2.70 [.079-.106]	YES	NO	4.5-5.0 [.177-.197]	1.20-1.32 [.047-.0512]	173707-[] ⁵	171662-[] ^{3 5}	ECONOSEAL "J" II, .070 Series Contacts	114-5082
	1.25-1.42 [16]					1.38-1.52 [.054-.060]				
91585-1 91585-3	0.50-0.89 [20-18]	2.00-2.70 [.079-.106]	YES	NO	4.5-5.0 [.177-.197]	1.20-1.32 [.047-.052]	173706-[] ⁵	171661-[] ^{3 5}	ECONOSEAL "J" II, .070 Series Contacts	114-5082
	1.25-1.42 [16]					1.38-1.52 [.054-.060]				


¹ LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.

2. AMP, CERTI-CRIMP and ECONOSEAL ARE TRADEMARKS.

³ TERMINAL MUST BE PRE-FORMED BEFORE IT CAN BE CRIMPED.

⁴ .070 TYPE RUBBER PLUG 172746-[] OR 178210-[] IS USED WHEN CRIMPING THIS PRODUCT.

⁵ .070 TYPE RUBBER PLUG 176886-[] OR 172888-[] IS USED WHEN CRIMPING THIS PRODUCT.



⁶ POSITION CONTACT BETWEEN CRIMPS SO LOCATOR / INSULATION STOP ENTERS THE CONTACT. PUSH THE CONTACT TOWARD THE LOCATOR AS SHOWN IN FIGURE 1. HOLDING CONTACT IN PLACE, SQUEEZE TOOL HANDLES TOGETHER UNTIL INSULATION BARREL ANVIL STARTS ENTRY INTO INSULATION CRIMPER. DO NOT DEFORM INSULATION BARRREL OR WIRE BARREL AT THIS MOMENT.

⁷ -1 IS A COMPLETE CERTICRIMP II HAND TOOL ASSEMBLY. -3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.

8. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.




CERTI-CRIMP II DATA SHEET

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWG: M. YOUNGER 21FEB2012		MATERIAL: -		HEAT TREAT: -	
mm		0 PLC ± -		CHK: E.A. WOLFE 22FEB2012					
		1 PLC ± -		APVD: E.A. WOLFE 22FEB2012					
		2 PLC ± -		NAME: E.A. WOLFE					
		3 PLC ± -							
		4 PLC ± -							
		ANGLES ±							
		SURFACE TEXTURE		✓					
P LTR		REVISION RECORD		DATE		DWG		APVD	
B4		REVISED - NEW FORMAT		2-2012		MY		BAW	
SCALE		SIZE		DRAWING NO		SHEET		REV	
-		A1		1583009		1		2 B4	

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS. IT IS NOT TO BE DISCLOSED TO ANYONE OTHER THAN THE PERSONNEL, WITHOUT AUTHORIZATION FROM TE. www.TE.com

LOC: A
DIST: 00




DIMENSIONING AND TOLERANCING PER ASME Y14.5M (1ST STANDARDS).
 THIS DRAWING IS A CONTROLLED DOCUMENT. DRAW NO. 1583009

TOOL NUMBER	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	INSUL. ADJ.	FLIP LOCATOR	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS 		CONTACT DESCRIPTION	APPLIC. SPECIF.
							LOOSE PIECE	STRIP FORM		
 -1 										
1752959-1	1.28-1.42 [16]	2.08-2.64 [.082-.104]	YES	NO	3.60-4.20 [.142-.165]	1.42 ± 0.05 [.056 ± .002]	-	1-1437709-3	1.6 MM SYSTEM TERMINAL W/SEAL	N/A
1752959-3	1.94-2.15 [14]					1.60 ± 0.05 [.063 ± .002]	-	1-1437709-6		
1752960-1	0.50-0.60 [20]	1.40-2.21 [.055-.087]	YES	NO	3.60-4.20 [.142-.165]	1.07 ± 0.05 [.042 ± .002]	-	1-1437709-2	1.6 MM SYSTEM TERMINAL W/SEAL	N/A
1752960-3	0.81-0.96 [18]					1.19 ± 0.05 [.047 ± .002]	-	1-1437709-5		
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TE CONNECTIVITY AND ITS AFFILIATES. IT IS NOT TO BE DISCLOSED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN AUTHORIZATION FROM TE CONNECTIVITY.

LOC: A
 DIST: 00

CERTI-CRIMP II DATA SHEET

DWN: M. YOUNGER 21FEB2012		MATERIAL: -		HEAT TREAT: -	
CHK: B.A. WOLFE 22FEB2012		APVD: B.A. WOLFE 22FEB2012		 TE Connectivity	
NAME: B.A. WOLFE		SCALE: -			
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± -		CERTI-CRIMP II TOOL DATA SHEET ECONOSEAL J-11 & .070 SERIES CONTACTS	
ANGLE: # - SURFACE TEXTURE: 		SCALE: - SIZE: A1 DRAWING NO: 1583009		SHEET: 2 of 2 REV: B4	