## 84 INCHES LENGTH



Connector A 112234 BNC Jack Straight Bulkhead - Rear Mount Brass Nickel 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122116 TNC Plug Straight Brass Nickel IP67 + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Con	nector A	Cable			Connector B	
D Ty G B C P P In M B B B IP C M	ype: BNC ender: Jack ody Type: Straight ontact Type: Crimp olarity: Standard npedance: 50 Ohm ounting: Bulkhead ody Material: Brass ody Finish: Nickel P Rating: None ontact Material: Beryllium ontact Finish: Silver ax. Freq.: 4 GHz	np BHD JK RG188 500 - Rear Mount Copper : Straight BHD	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 84 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	122116 TNC PLUG RG174 TNC Plug Straight Crimp Standard 50 Ohm Cable Brass Nickel IP67 Brass Gold 11 GHz TNC Plug Straight 0°	RG316 LMR100 50O
Amphenol		PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT.	THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		Title: BNC-ST-JK/TNC-ST-PL G174 84I   Part No: Q-040520003084i		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES