



Material

- Item ② Terminal body(metal housing): Brass(CuZn), Tin plated
- Item ⑤ Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Wire guard: Stainless steel
- Item ④ Insulator(housing): Thermoplastic (UL94V-0) BLACK

Electrical UL

- Voltage rating: 125V
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-26
- Stranded wire(AWG): 16-26
- Torque(Lb-In): 1.7Lb-In
- Screw: M2
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.25KV
- Operating temperature: -40°C to +115°C
- ② Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:

①	WSW P/N	DIM A
	A-TB350-TFxx	3.8
	A-TB350-TFxxBK-A	3.5

DIMENSION	
L	Nx3.5
B	(N-1)x3.5

UL approved WSW P/N		POLES	Tolerance (DimL&B)
③	A-TB350-TFxx	2p-5p	±0.15
	A-TB350-TFxxBK-A	6p-10p	±0.20
		11p-15p	±0.25
		16p-20p	±0.35
		21p-24p	±0.40

RoHS compliant
Unit: mm

File No.: E349947

Scale	Free
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

Id.	Modification	Date	Name
③	Delete P/N and add UL information	18.05.2021	Daniel
②	Update to new drawing and add UL	25.03.2016	Amy
①	Update	05.09.2011	Lucas
④	Drawn	19.04.2010	Alex

Date	Name
19.04.2010	Alex
18.05.2021	Daniel

ASSMANN
WSW components

Customer-No.
ASSMANN WSW-No. ③ A-TB350-TFxx A-TB350-TFxxBK-A
Drawing-No.
ASS 4092 CO rev03
Replace
Sheet 1/1