



NOTES: UNLESS OTHERWISE SPECIFIED.

1. SPECIFICATIONS:

- 1.1 FREQUENCY RANGE: DC TO 26.5 GHz
- 1.2 MAXIMUM INPUT POWER: 0.5 WATTS @ +25°C
DERATED LINEARLY TO 0 WATTS @ +125°C
- 1.3 OPERATING TEMP. RANGE: -55°C TO +125°C
- 1.4 IMPEDANCE: 50 OHM NOMINAL
- 1.5 VSWR (MAX.):
DC TO 18.0 GHz: 1.05 +0.008f (GHz)
18.0 TO 26.5 GHz: 1.30:1
- 1.6 FINISH: PASSIVATED STAINLESS STEEL

		Midwest Microwave	
	RoHS2 2011/65/EU	Title: TERMINATION	
<small>This PROPRIETARY Document is property of Emerson Network Power Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not tracked or copied without permission and is retrievable upon demand.</small> <small>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</small>	<small>UNLESS OTHERWISE SPECIFIED</small> .XX ±.02 .XXX ±.005 ANGLES ±2°	Model No. TRM-2443-F0-SMA-02	
	Size A	DO NOT SCALE DRAWING	Date: 1/16/2014