


REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		ECN-21-107697	30JUN2021	PZ WKH



ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Impedance (Ohm): <u>50</u> Frequency Range: <u>DC to 67GHz</u> Voltage Rating (Peak) @ Sea Level <u>150 V RMS</u> Insulation Resistance (MIN.) <u>5000 M ohms</u> Contact Resistance (mohms MAX) Center Contact <u>4.0</u> Outer Contact <u>1.0</u> Dielectric Withstand Voltage: <u>500 V RMS Max</u> Insertion Loss : TBD VSWR: <u>&lt;1.33 @ DC ~ 67GHz</u>	Interface Dimension <u>1.85mm male and 1.35mm male</u> Force to Engage and Disengage Engage: <u>N/A</u> Disengage: <u>N/A</u> Center Contact Captivation Axial (N) <u>26.0 MIN</u> Radial (In/Oz) <u>N/A</u> Cable Retention Axial (Lbs) <u>N/A</u> Mating cycles <u>500 cycles</u>	TEMPERATURE RANGE <u>-40 °C~+85 °C</u> ROHS <u>COMPLIANT</u>

1	SHELL	STAINLESS STEEL	PASSIVATION
1	CONTACT PIN	BERYLLIUM COPPER	GOLD 50 u"/NICKEL /COPPER
1	INSULATOR	PEI	N/A
1	BODY	STAINLESS STEEL	PASSIVATION
2385340-1	PART NUMBER	MATERIAL	PLATING

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	27JAN2021		TE Connectivity
		CHK	27JAN2021		
		APVD	27JAN2021		
		PRODUCT SPEC			
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± 0.3 2 PLC ± 0.2 3 PLC ± 0.1 4 PLC ± - ANGLES ± 5°		NAME 1.35mm Male to 1.85mm Male Adapter	
MATERIAL -		FINISH -		APPLICATION SPEC -	
		WEIGHT -		SIZE A2	
		CUSTOMER DRAWING		CAGE CODE 00779	
		SCALE 1:1		DRAWING NO C-2385340	
		SHEET 1 OF 1		RESTRICTED TO -	
		REV A			