



Digital Input Modules

8-channel 24 VDC digital input modules



M-1800: 8 digital inputs, sink type, 24 VDC

Digital Inputs: 8 channels
Type: sink
On-state Voltage: 24 VDC nominal, 11 to 28.8 VDC
Off-state Voltage: 0 to 5 VDC
On-state Current: 6 mA/point @ 28.8 VDC (max.)
Input Impedance: 5.1K ohms (typical)
Filtering Time: 1.5 ms (typical)
Common Type: External common (single common)
Power Consumption: 35 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O cable max. AWG14
MTBF: 15,759,240 hrs (Database: Telcordia/Bellcore)



M-1801: 8 digital inputs, source type, 24 VDC

Digital Inputs: 8 channels
Type: source
On-state Voltage: 24 VDC nominal, 11 to 28.8 VDC
Off-state Voltage: 0 to 5 VDC
On-state Current: 6 mA/point @ 28.8 VDC (max.)
Input Impedance: 5.1K ohms (typical)
Filtering Time: 1.5 ms (typical)
Common Type: External common (single common)
Power Consumption: 35 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O cable max. AWG14
MTBF: 15,811,800 hrs (Database: Telcordia/Bellcore)



16-channel 24 VDC digital input modules



M-1600: 16 digital inputs, sink type, 24 VDC

Digital Inputs: 16 channels
Type: sink
On-state Voltage: 24 VDC nominal, 11 to 28.8 VDC
Off-state Voltage: 0 to 5 VDC
On-state Current: 6 mA/point @ 28.8 VDC (max.)
Input Impedance: 5.1K ohms (typical)
Filtering Time: 1.5 ms (typical)
Common Type: 16 channels for 2 COMs (single common)
Power Consumption: 40 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O flat cable 20-pin
MTBF: 11,659,560 hrs (Database: Telcordia/Bellcore)





M-1601: 16 digital inputs, source type, 24 VDC

Digital Inputs: 16 channels
Type: source
On-state Voltage: 24 VDC nominal, 11 to 28.8 VDC
Off-state Voltage: 0 to 5 VDC
On-state Current: 6 mA/point @ 28.8 VDC (max.)
Input Impedance: 5.1K ohms (typical)
Filtering Time: 1.5 ms (typical)
Common Type: 16 channels for 2 COMs (single common)
Power Consumption: 40 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O flat cable 20-pin
MTBF: 11,694,600 hrs (Database: Telcordia/Bellcore)



4-channel AC digital input modules



M-1450: 4 digital inputs, 110 VAC

Digital Inputs: 4 channels, 110 VAC
On-state Voltage: 120 VAC nominal, 85 to 132 VAC
Off-state Voltage: 0 to 45 VAC
On-state Current: 8 mA/point @ 132 VAC (max.)
Input Impedance: 11K ohms (typical)
Common Type: 4 channels for 2 COMs (single common)
Power Consumption: 35 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O cable max. AWG14
MTBF: 19,482,240 hrs (Database: Telcordia/Bellcore)



M-1451: 4 digital inputs, 220 VAC

Digital Inputs: 4 channels, 220 VAC
On-state Voltage: 240 VAC nominal, 170 to 264 VAC
Off-state Voltage: 0 to 45 VAC
On-state Current: 12 mA/point @ 264 VAC (max.)
Input Impedance: 22K ohms (typical)
Common Type: 4 channels for 2 COMs (single common)
Power Consumption: 35 mA @ 5 VDC
Isolation: I/O to logic (photocoupler isolation)
Wiring: I/O cable max. AWG14
MTBF: 19,727,520 hrs (Database: Telcordia/Bellcore)



: Ordering Information

Available Models

- M-1800:** Modular remote I/O module with 8 DIs, sink type, 24 VDC, RTB, -10 to 60°C operating temperature
- M-1801:** Modular remote I/O module with 8 DIs, source type, 24 VDC, RTB, -10 to 60°C operating temperature
- M-1600:** Modular remote I/O module with 16 DIs, sink type, 24 VDC, 20-pin, -10 to 60°C operating temperature
- M-1601:** Modular remote I/O module with 16 DIs, source type, 24 VDC, 20-pin, -10 to 60°C operating temperature
- M-1450:** Modular remote I/O module with 4 DIs, 110 VAC, RTB, -10 to 60°C operating temperature
- M-1451:** Modular remote I/O module with 4 DIs, 220 VAC, RTB, -10 to 60°C operating temperature