

IE-S1DS2VE0400T01T01-E

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Single pair Ethernet is a technology that only requires one pair of wires to transmit data and power. The resulting benefits will make SPE the preferred network at the field level and beyond.

Advantages of Single Pair Ethernet

- **Consistent:** Single Pair Ethernet enables uniform Ethernet-based communication from the sensor to the cloud
- **Future-proof:** key technology for Industry 4.0 and IIoT
- **Flexible:** ranges of up to 1000 m and transmission properties of up to 1 Gbps enable use across applications
- **Innovative:** lighter, less space required, and reduced installation effort

General ordering data

Version	Patch cable, SPE plug (IEC 63171-2) - IP20 socket contact - straight, SPE plug (IEC 63171-2) - IP20 socket contact - straight, PVC, 40 m
Order No.	2725850400
Type	IE-S1DS2VE0400T01T01-E
GTIN (EAN)	4064675364412
Qty.	1 pc(s).

IE-S1DS2VE0400T01T01-E**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Length	40 m	Length (inches)	1,574.803 inch
Net weight	400 g		

Temperatures

Operating temperature	-40 °C...80 °C
-----------------------	----------------

Electrical properties

Dielectric strength, contact / contact	1000 V DC	Dielectric strength, contact / shield	2250 V DC
PoE / PoE+	PoDL acc. to IEEE 802.3bu / cg		

Standards

Connector standard	IEC 63171-2
--------------------	-------------

Cable structure

Colour coding	white / blue	Complete shielding	Shielding braid made from copper wiring
Cross-section	2*AWG 22	Insulation	PE
Insulation diameter 2	1.65 mm	Material sheath	PVC
Number of wires	2	Overlap of shielding braid	80 %
Sheath diameter, max.	5.3 mm	Sheath diameter, min.	4.9 mm
Shielding	STP	Strands	7

Electrical properties of cable

Capacity at 800 Hz	1.6 nF/km	Characteristic impedance	100 ± 15 Ω at 20 MHz
Coupling attenuation 1 to 600 MHz	Type I	Rated current	3.5 A
Rated voltage (DC)	60 V	Resistance differential	2 %
Test voltage: wire-wire-shield	1 kV DC, 1 min	Transmission rate	10/100 MBit/s, 1000 MBit/s

Mechanical and material properties of cable

Bending radius	20 mm	Colour	black
Halogen	Yes	Resistance to oils	IRM 902/903 oil resistance test at (70°Cx4h)
Resistance to spread of flame	FT1	UV-resistant	Complies with UL 1581 Sec. 1200

Plug, left

Connector left	SPE plug (IEC 63171-2) - IP20 socket contact - straight
----------------	--

Plug, right

Connector right	SPE plug (IEC 63171-2) - IP20 socket contact - straight	Housing main material	Elastollan
-----------------	--	-----------------------	------------

Creation date March 11, 2022 7:13:55 PM CET

Catalogue status 11.02.2022 / We reserve the right to make technical changes.

2

IE-S1DS2VE0400T01T01-E

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

plug

Connector left	SPE plug (IEC 63171-2) - IP20 socket contact - straight	Connector right	SPE plug (IEC 63171-2) - IP20 socket contact - straight
----------------	---	-----------------	---

Classifications

ETIM 6.0	EC002599	ETIM 7.0	EC002599
ETIM 8.0	EC002599	ECLASS 9.0	27-06-03-08
ECLASS 9.1	27-06-03-08	ECLASS 10.0	27-06-03-08
ECLASS 11.0	27-06-03-08		

Downloads

Catalogues [Catalogues in PDF-format](#)

Data sheet

IE-S1DS2VE0400T01T01-E

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Detailed drawing

Dimensional drawing

