


- About IDT
- Products
- Applications
- Getting
- mvIDT

[Home](#) > [Products](#) > > [VPP1500](#) > VPP1500BFG8

You may also like...

VPP1500BFG8

Category:
Generic Part: [VPP1500](#)
Market Group: VIDEO
Description: DUAL LVDS TCON



Parameters

| | |
|-------------------------|--------|
| Speed | NA |
| Temperature | C |
| Voltage | 1.8 V |
| Status | Active |
| Sample | Yes |
| Minimum Order Quantity | 1000 |
| Factory Order Increment | 1000 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

No documents available for this part at this time.

Package

| | |
|----------------------------------|--|
| Package | CABGA 289 (BFG289) |
| Description | CHIP ARRAY BGA 15MM X 15MM X 0.8MM PITCH |
| Status | Active |
| Class | PLASTIC |
| Category | Green |
| Pb (Lead) Free | Yes |
| Mark | BFG |
| Package Type | CABGA |
| Lead Count | 289 |
| Length | 15.0 mm |
| Width | 15.0 mm |
| Thickness | 1.4 mm |
| Pitch | 0.8 mm |
| Tube / Tray | TRAY |
| Quantity per Tube/Tray | 112 |
| Quantity per Reel | 1000 |
| Moisture Sensitivity Level (MSL) | 3 |
| Moisture Exposure Floor Life | 168hrs@<30C/60%RH |
| Peak Reflow Temperature | 260Â°C |
| Rebake Conditions | 48hrs@125C |
| Related Package Documents | view documents |