


HC-M-PN2-6,00-BU-V

Order No.: 1676776

The illustration shows versions, pneumatic male, female and female with valve

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1676776>Pneumatics female connector with valve, for HC-M-PN2 module, cross
section of hose 6.0 mm

Commercial data	
GTIN (EAN)	 4 017918 129408
sales group	D044
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 463 (PC-2009)

Product notesWEEE/RoHS-compliant since:
05/19/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Electrical characteristics**

Ambient temperature (operation) -40 °C ... 125 °C

Mechanical characteristics

Operating pressure, vacuum 6.00 bar

Internal diameter of pressure hose connection 6 mm

Insertion/withdrawal cycles ≥ 500 **General characteristics**

Color black

Material data

Contact material	Delrin acetal
------------------	---------------

Certificates / Approvals



Certification

GOST, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;