Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Disconnect switch, TeSys VLS, protruding rotary handle, hole mounting, 65x65 mm, black handle, 5 mm shaft, defeatable

VLSH2H5BD

V	aı	n

Range	TeSys
Device short name	VLSH
Product or component type	Rotary handle
Range compatibility	TeSys (TeSys VARIO LS) VLS3P
Handle colour	Black
Handle front plate colour	Grey
Rotary handle padlocking	1 to 3 padlocks 0.160.31 in (48 mm)
Marking	0 - 1

#### Complementary

Fixing mode	Hole 0.89 in (22.5 mm)
Tightening torque	20.36 lbf.in (2.3 N.m)
Base dimension	65 x 65 mm
Height	2.56 in (65 mm)
Width	2.56 in (65 mm)
Depth	2.85 in (72.5 mm)
Product weight	0.14 lb(US) (0.064 kg)

### **Environment**

IP degree of protection	IP65
NEMA degree of protection	NEMA 1
	NEMA 2 UL 508
	NEMA 3R UL 508
	NEMA 4 UL 508
	NEMA 4X UL 508
	NEMA 12 UL 508
	NEMA 12K UL 508

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.17 in (5.5 cm)
Package 1 Width	2.56 in (6.5 cm)

Package 1 Length	2.56 in (6.5 cm)
Package 1 Weight	2.22 oz (63 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	6.56 lb(US) (2.975 kg)

# Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
RoHS exemption information	Yes	

## Recommended replacement(s)