

2404183

https://www.phoenixcontact.com/us/products/2404183

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Maintenance license (1 year) for the SUP-10 Emalytics Supervisor license

### Commercial data

Item number	2404183
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DR18
Product key	DRHBAA
GTIN	4055626349336
Weight per piece (including packing)	0.001 MGM
Weight per piece (excluding packing)	0.001 MGM
Customs tariff number	49119900
Country of origin	US



2404183

https://www.phoenixcontact.com/us/products/2404183

### Technical data

### Product properties

Languages supported

Screen resolution

oddot properties	
Product type	Building management system
Area of application	Building technology
stem properties	
Type of software	On-premise
Intended use for the software	Automation
	Engineering
License information	
Type of license	Maintenance license
License duration	1 Jahr
Functionality	
Integrated function	Analysis
	Data acquisition
	Data acquisition  Diagnostics
	Diagnostics
	Diagnostics Startup
	Diagnostics Startup Communication
	Diagnostics Startup Communication Configuration
Target system	Diagnostics Startup Communication Configuration Project planning
Target system Supported controllers	Diagnostics Startup Communication Configuration Project planning Simulation
	Diagnostics Startup Communication Configuration Project planning Simulation Server

German, English

1024 x 768 pixel(s) ,or higher



2404183

https://www.phoenixcontact.com/us/products/2404183

### Classifications

UNSPSC 21.0

### **ECLASS**

27242590
27242590
27242590
EC001435

43233600



2404183

https://www.phoenixcontact.com/us/products/2404183

#### Accessories

ILC 2050 BI - Controller

2403160

https://www.phoenixcontact.com/us/products/2403160



Modular Inline controller for automation applications in the fields of building technology, infrastructure, and energy technology. Equipped with two logically separated IP address interfaces each with 2 integrated Fast Ethernet ports. Configurable assignment of the Ethernet ports for the use of the spanning-tree protocol, daisy chain and redundant ring structures for maximum availability. Four LAN, two USB, and two RS-485 interfaces are integrated. The data point connections can be extended with up to 63 Inline I/O modules: digital and analog, function terminals for DALI, pulse counting, MBUS or serial interfaces.

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com