

/stal Series NOCK

Model C8

4 PADS 3.2 x 2.5



Frequency Range: 1.00MHz to 156.25MHz / 32.768KHz

Features

- High reliability & low cost unit

- Tight stability & extended temperature available Lead-free type For automotive applications, please contact our sales representatives


Standard Specifications

QUARTZ

CRYSTALS

ltem		Value	
Frequency Range	1.00MHz t	1.00MHz to 156.25MHz / 32.768KHz	768KHz
Frequency Stability	±5	±50ppm (or specify)	
Operating Temperature Range	-20°C	-20°C to +70°C (or specify)	fy)
Operable Temperature Range		-40°C to +85°C	
Operating Voltage	1.8\	1.8V / 3.3V / 5.0V ±10%	6
Output Type		HCMOS	
Output Load		15pF Max.	
Current Consumption (Max)	1.8V:	3.3V	5.0V
	1-16MHz: 5mA 17-80MHz: 12mA	1-16MHz: 7mA 17-80MHz: 20mA	1-16MHz: 15mA 17-60MHz: 35mA
	81-156.25MHz: 20mA 81-156.25MHz: 20mA 32.768KHz: 0.2mA 32.768KHz: 0.2mA	81-156.25MHz: 20mA 32.768KHz: 0.2mA	
Output Symmetry	HCMOS: 40~60%	HCMOS: 40~60%(at 50%V _{DD}); 45~55% is available	5% is available
"High" Output Voltage	HC	HCMOS: 90%V _{DD} Min.	
"Low" Output Voltage	HC	HCMOS: 10%V _{DD} Max.	
Rise and Fall Time	1.8V / 3.3V		5.0V
	1-156.25MHz: 7ns Max		1-60MHz: 10ns Max.
	32.768KHz: 30ns Max	X	
Tri-State		Yes	
		100	

Dimension





- 1. Manufacturer reserves the right to change the specification and content of this product for improvement without notification. 2. Custom specification is welcome. Please contact our sales representative for further details.
- 3. If the crystal is intended for applications which have direct impact on human life and properties, and require a high degree of reliability and safety concerns, customers must provide full information such as but not limit to the application, electrical and reliability specification at the inquiry beginning stage

