

Aug. 1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	△ CABLE DIAMETER : φ6.9±0.5	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△	1	DIS-E-00011415	KIM JAEHYEON	KG. OKITA	20221013
REMARK Unless otherwise specified, refer to JIS C 5402.			APPROVED	AO. SUZUKI	20090507
			CHECKED	KN. ICHIKAWA	20090507
			DESIGNED	MO. SHIMOYAMA	20090507
			DRAWN	MO. SHIMOYAMA	20090507
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-126674-00	
HRS	SPECIFICATION SHEET		PART NO.	DH-27-CMB (6. 9)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0244-0036-9-00	△ 1/1