

## **REAR VIEW**

Configuration	Features	VMtr, AMtr, Srg	Physical	Dimensions	63" H x 2" W x 3" D	,
	Layout	Zero U		Materials	Chassis: Steel	
				Finishes	Chassis: Painted Bl	ack, F
Input 1	Voltage	100-120 Vac, Single Phase, 50/60 Hz				
	Max Current	30 Amps	Operating	Temperature	32°F to 122°F	
	Max Load	2.88 KVA		Humidity	5 %RH to 85 %RH	
				Elevation	6,562 feet	
	Connection	L5-30P, 9 ft cord, 3-wire 10 ga, SJT jacket (Bottom panel)				
	Voltage Monitor	Digital	Conformance	Warranty	http://www.marwa	
	Current Monitor	Digital		Safety Certifications	UL, CUL, CE, RoHS	
				Environment Certifications	None	
Outlets	All Panels [1][2]	(30) 5-20R, 110-120V				
			Notes:			
Protection	Spike/Surge Suppression [1]	Yes		Is of the circuitry may only be re-	•	atic (a
	EMI Filter [1]	None	[2] S = switched,	V = monitored voltage, A = mon	itored amps	
	Over Current [1]	(2) 20A Circuit Breaker				
Env Sensors	Temperature	None				
	Humidity	None				
	Interlocks	None				
	EPO	None			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MILLIMETERS] TOLERANCES ARE:	
					ANGLES DECIMALS ± .5' .XX ± .03 .XXX ± .010	м
Communications	Display	Multi-function Controller			DO NOT SCALE DRAWING	
	Serial	None				CHECKE
	Ethernet	None				APPROV
	Protocols	None			FINISH:	THE
						THE IN IS THE S ANY R WI MARWAY

В

А

