



REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN APVD
	A	OBSOLETE -3 (ECO-20-009897)	01MAR2021	A.L H.L



NEEDING THE COVER TAPE  
AROUND THE OUTER  
PERIPHERY IN  
A TURN.

QTY	HEIGHT TYPE	H	G	F	E	D	C	B	A	POS	CONN P/N	PART NO.
2	OBSOLETE											
	OBSOLETE	400	17	16				58	72	68.4	34.2	120
	OBSOLETE							42	56	52.4	26.2	80
	OBSOLETE	600	8H	8.8	12	7.85	8.25	34	44	40.4	20.2	60
	OBSOLETE							58				120
	OBSOLETE	450	17	16				42	56	52.4	26.2	80
	OBSOLETE							34	44	40.4	20.2	60
	OBSOLETE	700	7H	8.8	12	6.85	7.25	26	44	40.4	20.2	40
	OBSOLETE							58				120
	OBSOLETE	550	17	16				42	56	52.4	26.2	80
	OBSOLETE							34	44	40.4	20.2	60
	OBSOLETE	800	6H	8.8	12	5.85	6.25	26	44	40.4	20.2	40
	OBSOLETE							58				120
	OBSOLETE	650	17	16				42	56	52.4	26.2	80
	OBSOLETE							34	44	40.4	20.2	60
	OBSOLETE	900	5H	8.8	12	4.85	5.25	26	44	40.4	20.2	40

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	0 PLC ± -
	1 PLC ± 0.3
	2 PLC ± 0.25
	3 PLC ± 0.2
	4 PLC ± -
	ANGLES ± 3'
MATERIAL	FINISH
-	-

DWN	FLORENCE TAN	20SEP04
CHK	ERIC TNG	
APVD	SF LFONG	
PRODUCT SPEC		
APPLICATION SPEC		
WEIGHT		
CUSTOMER DRAWING		



PLUG ASS'Y WITH SOLDER PEG,  
FH 0.8mm B-T-B CONN.  
STACK HEIGHT 5mm, ON TAPING

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=5179161	-
SCALE	SHEET	REV	
2:1	1 OF 1	A	

NOTE:  
1. THIS PRODUCT WAS COATED BY FLUX-PENETRATION  
-INHIBITING AGENT.

**2** OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI