ADT-2804-NF-HNM-02 NOTES: UNLESS OTHERWISE SPECIFIED. NUMBER 1. MATERIALS & FINISH: 1.1 HOUSING & NUT: PASSIVATED STAINLESS STEEL 1.2 CENTER CONTACT: GOLD PLATED BERYLLIUM COPPER 1.3 DIELECTRIC: PTFE (TEFLON) 1.4 GASKET: SILICONE RUBBER 1.62 2. ELECTRICAL SPECIFICATIONS: 2.1 FREQUENCY RANGE: DC TO 8 GHz 2.2 VSWR (MAX): DC TO 4 GHz: 1.08:1 4 TO 8 GHz: 1.20:1 2.3 IMPEDANCE: 50 OHMS NOMINAL 3. MECHANICAL: CENTER CONTACT CAPTURED IN ACCORDANCE WITH MIL-A-55339 HN PLUG PER -TYPE N JACK PER MIL-STD-348, FIG. 317-1 MIL-STD-348, FIG. 304-2

REV.	DESCRIPTION	DAIE
A1	ECO 23144	1/3/11
В	ECO 25449	9/28/15

This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is no MIDWEST MICROWAVE traced or copied without ermission and is returnable TITLE INTERPRET DRAWING ACCORDANCE WITH ASME Y14.5-2009. ADAPTER UNLESS OTHERWISE NOTED TYPE N JACK TO HN PLUG DIMENSIONS ARE IN INCHES CONNECTIVITY SOLUTIONS AND TOLERANCES ARE: a bel group 3 PLACE DECIMALS ±.005 2 PLACE DECIMALS ±.02 ENG./DATE A. OSGA 12/15/94 DRAWN/DATE A. BEATTY FRACTIONS ±1/64 DRAWING NUMBER PARALLELITY: T.I.R. _ 12/13/94 ADT-2804-NF-HNM-02-01 FLATNESS: T.I.R. _ APPROVED/DATE
J. KEREKES
9/28/15 CHECKED/DATE
M. HOLLMAN CONCENTRICITY: T.I.R. _

12/15/94

ANGLES AND PERPENDICULARITY: ±1°

REV.

В

1 of

5 = 1

SCALE:

SHEET