

ROL0 No-Clean Tack Flux in a 3cc/3g Luer Lock Manual Syringe w/tips

Product Highlights

More Robust, Higher Activity, Better Wetting, No-Clean
 Ideal for all rework, solder, de-solder and reflow applications
 Non-corrosive, non-conductive
 Tack flux will not run all over PCB when applied
 Has a pleasant odor
 Excellent wetting
 Easily cleaned with isopropyl alcohol (IPA)
 Attachment of BGA spheres
 Soldering flip chip components
 Long stencil life
 Wide process window
 Clear residue
 Can be used with Leaded and Lead-Free applications
RoHS 3 and REACH compliant



Representative Photo Only
 Please note flux color may vary
 from light yellow to orange/brown

Specifications

Flux Type:	Synthetic No-Clean (for Leaded and Lead-Free applications)
Flux Classification:	ROL0
Flux Activation Temperature:	140°C (284°F)
Color:	Light yellow to orange/brown
Packaging:	3cc/3g Luer Lock Manual Syringe w/tips
Shelf Life:	Refrigerated >24 months, Unrefrigerated >24 months

Stencil Life

>8 hours @ 20-50% RH 22-28°C (72-82°F)
 >4 hours @ 50-70% RH 22-28°C (72-82°F)

Stencil Cleaning

Automated stencil cleaning systems for both stencil and misprinted boards. Manual cleaning using isopropyl alcohol (IPA).

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). Do not freeze. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Conforms to the following Industry Standards:

J-STD-004B, Amendment 1 (Solder Fluxes):	Yes
RoHS 3 Directive (EU) 2015/863:	Yes