

## Flexible RF cable

**S\_10162\_B-11** Item: 23002145

### Description

S: Low loss RF cables with foam PE dielectrics

50 Ohm, 8 GHz, 85°C, ø12.9 mm, LSFH jacket, Flame retardant, Railway qualified



### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Copper clad Aluminum	Wire	3.8 mm
Dielectric	SPE (Foamed Polyethylene)		9.9 mm
Outer conductor	Copper	longitudinal Foil, 100%	10 mm
Outer conductor	Copper	Braid, 80 %	10.8 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	12.9 mm +/- 0.2

Print: HUBER+SUHNER S 10162 B-11 50 Ohm (production order number)

#### Electrical Data

Impedance		50 Ω +/- 2
Operating Frequency		8 GHz
Capacitance		77 pF/m
Velocity of signal propagation		87 %
Signal delay		3.85 ns/m
Screening effectiveness		≥ 90 dB (up to 7.5 GHz)
Operating voltage		≤ 1.7 kV <sub>rms</sub> (at sea level)
Test voltage		3.4 kV <sub>rms</sub> (50 Hz/1 min)
Phase vs Temperature	-40°C... + 70°C	3000 ppm
Phase vs Bending		2 °/GHz

#### Mechanical Data

Weight		15 kg/100 m
Min. bending radius	static	100 mm 200 mm

#### Environmental Data

Temperature range	-40 °C ... +85 °C
Installation temperature	-20 °C... +60 °C
Uv resistance test	ISO 4892-2A
Flame propagation test	IEC 60332-1, EN 60332-1-2, EN 50266-2-4, IEC 60332-3-24, BS 4066-3, NF C 32-070 C2
Smoke density test	EN 61034-2
Toxicity test	BS 6853 Annex B
Halogen test	IEC 60754
Halogen free	Yes
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant
2000/53/EC (ELV)	compliant
2012/19/EU (WEEE)	no special marking needed

### Additional Information

EN 45545-2 compliant hazard level for indoor cables: HL3 NFPA-130 compliant An operating temperature of -55°C is feasible for static applications.

#### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

#### Suitable Connectors

Cable group S39 10 mm / 50 Ohm

## Flexible RF cable

**S\_10162\_B-11**    **Item: 23002145**

**Matrix**      typical Attenuation [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] and maximum Power CW [ formula:  $(p/f^{0.5})$  ]

Coefficients:

a = 0.0826

b = 0.0129

f<sub>max</sub> = 8

P at 1GHz = 700

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0.4	0.06	0.017	1107
0.8	0.08	0.026	783
1.2	0.11	0.032	639
1.6	0.13	0.038	553
2.0	0.14	0.043	495
2.4	0.16	0.048	452
2.8	0.17	0.053	418
3.2	0.19	0.058	391
3.6	0.2	0.062	369
4.0	0.22	0.066	350
4.4	0.23	0.070	334
4.8	0.24	0.074	320
5.2	0.26	0.078	307
5.6	0.27	0.082	296
6.0	0.28	0.085	286
6.4	0.29	0.089	277
6.8	0.3	0.092	268
7.2	0.31	0.096	261
7.6	0.33	0.099	254
8.0	0.34	0.103	247