



- △ 25.4um[.000100] MIN TIN-LEAD OVER 1.27um[.000050] MIN NICKEL.
- △ 0.76um[.000030] MIN GOLD, INTERNALLY, FOR A DISTANCE OF 5.08[.200] MIN FROM MATING END, GOLD FLASH ON THE REMAINDER, ALL OVER 0.76um[.000030] MIN NICKEL.
- △ POSTS ARE SEMI AUTOMATICALLY WIREABLE AND WILL ACCOMMODATE 3 TERMINATIONS.
- △ ALTERNATE DIMENSION FOR USE WITH JACKSCREWS.
- △ AMP, PART NUMBER AND DATE CODE INK STAMPED IN THIS AREA.
- 6. #24 AWG MAX WIRE TO BE USED WITH THIS CONNECTOR.
- △ 25.4um[.000100] MIN TIN OVER 1.27um[.000050] MIN NICKEL.

△	205359-8
△	205359-1
POST FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. REIFSNYDER 09 FEB 96		Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R. STONE 22 FEB 96		APVD M. MCALONIS 22 FEB 96	NAME SOCKET ASSY, 104 POSN, AUTOWIREABLE, STANDARD M SERIES
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		APPLICATION SPEC	
0 PLC ± - 1 PLC ± - 2 PLC ± 0.13 [.005] 3 PLC ± - 4 PLC ± - ANGLES ± -		WEIGHT		SIZE A1	
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS		CUSTOMER DRAWING	
		SCALE 2:1		SHEET 1 OF 1	
		REV T		DRAWING NO. 00779 ©=205359	