

DEUTSCH | DEUTSCH DT

TE Internal #: DT3P-DC

Automotive Connector Caps & Covers, Protective Cover, Gray,

PVC, 3 Position, -20 – 212 °F [-29 – 100 °C]

View on TE.com >



Connectors > Automotive Connectors > Automotive Connector Accessories > Automotive Connector Caps & Covers > Dust Caps — DEUTSCH DT











Protection & Strain Relief Accessory Type: Protective Cover

Strain Relief: Without

Primary Product Color: **Gray**Primary Product Material: **PVC**

Number of Positions: 3

All Dust Caps — DEUTSCH DT (12)

Features

Product Type Features

Product Type Features	
Protection & Strain Relief Accessory Type	Protective Cover
Sealable	No
Configuration Features	
Number of Positions	3
Body Features	
Primary Product Color	Gray
Primary Product Material	PVC
Mechanical Attachment	
Strain Relief	Without
Usage Conditions	
Compatible With Connector Style	Receptacle
Operating Temperature (Max)	100 °C[212 °F]

-29 - 100 °C[-20 - 212 °F]

Operating Temperature Range



Industry Standards	
Degree of Protection	Not Tested
Packaging Features	
Packaging Method	Box
Other	
Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts








Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers (107)



Automotive Connector Locks & Position Assurance(74)



Automotive Housings(619)



Automotive Seals & Cavity Plugs(6)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(20)




PCB Headers & Receptacles(103)

Customers Also Bought



TE Part #DT04-3P-E008

DEUTSCH DT Receptacle Connectors



TE Part #174259-2 ECONO-J MK-2 CAP HSG 4P




TE Part #DT4P-DC
PROTECT CVR, 4P, REC, GRY, DT





TE Part #776540-1 776310-1 SECONDARY LOCK WITH 120 OHM 1/2



TE Part #171661-2 E-J MK-2 070 TAB CONT



TE Part #EL7664-000 TMS-CT-50M-3/8-OUT-9



TE Part #852140-1 ANVIL, RIGHT (DUAL)





Documents

Product Drawings

PROTECT CVR, 3P, REC, GRY, DT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DT3P-DC_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DT3P-DC_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT3P-DC_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English