



**NOTES:**

- 1. MATERIAL: COPPER ALLOY
- 2. PLATING:

- (b) ITEM 1+2: GOLD FLASH over NICKEL
- ITEM 3: NICKEL PLATED

- 3. CRIMPING: USE CRIMP TOOL 360X10409X

WITH TOOL INSERT 360X20029X

SELECTOR SETTINGS: 3 FOR AWG 16

2 FOR AWG 18

2 FOR AWG 20

Directive 2002/95/EC RoHS compliant

(b)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish:				tolerance		scale:			
see notes				ISO 2768-m		5:1			
				dim. in mm		material:			
						see notes			
				date		title:			
				name		HIGH POWER CONTACT MALE			
				drawn 25.07.06		CRIMP VERSION 10A			
				appd. 26.07.06		D-SUB COMBINATION			
				norm		dwg no:			
				d-old		Inventor 10			
2 x b Ä3854 19.01.2011 K.H.						DIN-A4			
a Origin						13K1A1834		sh: 1	
rev. description date name						part no:		131A11019X	

