



NOTE: 1. ELECTRIC PERFORMANCE: (オ酥 ヤトフ)  
 DIELECTRIC STRENGTH: 500 V DC/0.01Sec.(ス筋絶ノカネヨアチ00V/0.01テ  
 INSULATION RESISTANCE: 100M OHMS Min.(セ オラ 絶ケラ 隔100ユラナキ)  
 CONDUCTIVE RESISTANCE: 2 OHMS Max.(オシフ 絶ケラ 第0ナキトキ)  
 2.S-ATA HOUSING:  
 POLYESTER(PBT),UL94V-0(BLACK)

68561-0019	679260002	30u" Gold -plated terminal
68561-0018	679260001	Gold flash terminal
MOLEX P/N	S-ATA CONN.	DESCRIPTION

G	COVER 679261040	1	
F	S-ATA CONN.: SEE TABLE	1	
E	4P CONTACT 887899491	4	
D	4P PWR HOUSING 887899490	1	
C	UL1007 #18 RED 887711301	1	144
B	UL1007 #18 BLK 887711300	2	288
A	UL1007 #18 YEL 887711303	1	144
ITEM	DESCRIPTION	QTY	L(mm)

ENTER DESCRIPTION EC NO: CPG2014-1666 DRWN: JXIA004 CHKD: GXYANG APPR: FNIE	DESCRIPTION 2013/12/04 2013/12/04 2013/12/09	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION				
					DRAWN BY GXYANG	DATE 04/08/10	TITLE S-ATA IDT POWER LATCHING ADAPTER CABLE ASSEMBLY 6 INCH (5V+12V)						
					CHECKED BY TEDDY	DATE 04/08/10	APPROVED BY BORON		DATE 04/08/10	MATERIAL NO. 685610018/9		DOCUMENT NO. SD-68561-003	SHEET NO. 1 OF 1
					ANGULAR ±---°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A4		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		