



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 54.8 mm, Rated cross-section: 6 mm<sup>2</sup>, Colour: Yellow

**RAL:** 1026

### **Business data**

Article number	17226.8
Article name	SQI 6/7 YE
GTIN (EAN)	4044211148799
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	8 g
Weight per piece (including packaging)	8.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17226.8
Product description	Insulated cross-connector



### **Technical data**

Dimensions	
Length	4 mm
Width	54.8 mm
Height	23 mm
Pitch size	8 mm
Ratings	
Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	41 A
Current load, max.	41 A
Rated cross-section	6 mm <sup>2</sup>
Contamination degree	2
Connection data	
No. of poles	7
Materials	
Material	Copper alloy
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	$\checkmark$
Touch protection is available	$\checkmark$
Number of bridged terminals	7
Environmental Product Compliance	
REACH Conform	Yes
REACH Candidate Substance Note	No
RoHS Conform	Yes

Media





### Accessories

#### Insulation cap for cross-connector

Insulating cap,	Colour: Yellow		
Article number	Article name	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10 YE	4044211148539	20

#### ##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17523.2	SPTK 6/LT/HB BG	4044211209223	50 ST



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17524.2	SPTK 6/LT/STBI/YE BG	4044211209919	50 ST

Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17151.4	SSIK 6/2A BK	4044211188993	50 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Black

Article numbe	r Article name	GTIN (EAN)	Packaging unit
17176.4	SSIK 6/2A/LED 30-60V AC/DC BK	4044211188931	50 ST



Fuse-disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm<sup>2</sup>, Width: 8.1 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
17178.4	SSIK 6/2A/LED 500V AC/DC BK	4044211188948	50 ST



### ##INVERSE##CONTA-CONNECT

Rated cross-se	ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou	ur: Beige	I TS 35/7.5,
Article number	Article name	GTIN (EAN)	Packaging unit
17520.2	SPTK 6/DU BG	4044211209650	50 ST
	ct terminal, Screw connection, Mour ection: 6 mm², Width: 8.1 mm, Colou	•••••••••••••••••••••••••••••••••••••••	I TS 35/7.5,
Article number	Article name	GTIN (EAN)	Packaging unit
17521.2	SPTK 6/LT BG	4044211209162	50 ST
	ct terminal, Screw connection, Mour ection: 6 mm², Width: 8.1 mm, Colou	•••••••••••••••••••••••••••••••••••••••	I TS 35/7.5,
Article number	Article name	GTIN (EAN)	Packaging unit
17522.2	SPTK 6/QT BG	4044211209216	50 ST
Rated cross-se	ct terminal, Screw connection, Mour ection: 6 mm², Width: 8.1 mm, Colou	ur: Beige	
Article number	Article name	GTIN (EAN)	
Article number 17525.2	Article name SPTK 6/LT/STBI/BU BG	GTIN (EAN) 4044211209926	50 ST
17525.2 Fuse-disconne		4044211209926 nting type: Mounting ra	unit 50 ST il TS 35/7.5,
17525.2 Fuse-disconne Rated cross-se	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou	4044211209926 nting type: Mounting ra ur: Black	unit 50 ST ill TS 35/7.5, Packaging
17525.2 Fuse-disconne Rated cross-se Article number 17175.4 Fuse-disconne	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name	4044211209926 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 nting type: Mounting ra	unit 50 ST iil TS 35/7.5, Packaging unit 50 ST
17525.2 Fuse-disconne Rated cross-se Article number 17175.4 Fuse-disconne	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou	4044211209926 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 nting type: Mounting ra	50 ST il TS 35/7.5, Packaging unit 50 ST
17525.2   Fuse-disconne   Rated cross-se   Article number   17175.4   Fuse-disconne   Rated cross-se	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou	4044211209926 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 nting type: Mounting ra ur: Black	unit 50 ST ill TS 35/7.5, Packaging unit 50 ST ill TS 35/7.5, Packaging
17525.2   Fuse-disconne   Rated cross-se   Article number   17175.4   Fuse-disconne   Rated cross-se   Article number   17175.4   Fuse-disconne   Rated cross-se   Article number   17177.4   Protective earther	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mou ection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name	4044211209926 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188955 nting type: Mounting rai	unit 50 ST iil TS 35/7.5, Packaging unit 50 ST iil TS 35/7.5, Packaging unit 50 ST
17525.2   Fuse-disconne   Rated cross-se   Article number   17175.4   Fuse-disconne   Rated cross-se   Article number   17175.4   Fuse-disconne   Rated cross-se   Article number   17177.4   Protective earther	SPTK 6/LT/STBI/BU BG ect terminal, Screw connection, Mourection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 12-30V AC/DC BK ect terminal, Screw connection, Mourection: 6 mm <sup>2</sup> , Width: 8.1 mm, Colou Article name SSIK 6/2A/LED 110-250V AC/DC BK th terminal, Screw connection, Moure	4044211209926 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188924 nting type: Mounting ra ur: Black GTIN (EAN) 4044211188955 nting type: Mounting rai	unit 50 ST iil TS 35/7.5, Packaging unit 50 ST iil TS 35/7.5, Packaging unit 50 ST



#### ##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
17132.2	SRK 6/2A/PE BKYE	4044211200718	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17109.2	SRK B 6/2A BG	4044211141745	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17108.2	SRK 6/2A BG	4044211141738	100



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17110.2	SRK 6/2A/Z BG	4044211141752	100 ST



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17117.2	SRK 6/2A SAS BG	4044211149000	80



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
87805.2	SRK 6/2A Ex BG	4044211199777	100

#### ##INVERSE##CONTA-CONNECT



