

## Cutting, stripping and crimping tool STRIPAX PLUS 2.5 ZERT

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



### Cutting, stripping and crimping tools for connected wire-end ferrules strips

- Cutting
- Stripping
- Crimping
- Automatic feeding of wire end ferrules
- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation
- Efficient: only one tool needed for cable work, and thus significant time saved

#### General ordering data

|            |  |
|------------|--|
| Order No.  | <a href="#">9011980000</a>   |
| Type       | STRIPAX PLUS 2.5 ZERT  |
| Version    | Cutting, stripping and crimping tool, Crimping tool for wire-end ferrules, 0.5 mm <sup>2</sup> , 2.5 mm <sup>2</sup> , Trapezoidal crimp |
| GTIN (EAN) | 4008190004613  |
| Qty.       | 1 pc(s).   |

**Cutting, stripping and crimping tool  
STRIPAX PLUS 2.5 ZERT**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |        |        |       |
|------------|--------|--------|-------|
| Length     | 210 mm | Weight | 260 g |
| Net weight | 260 g  |        |       |

**Contact description**

|                      |                                    |                      |                     |
|----------------------|------------------------------------|----------------------|---------------------|
| Type of contact      | Strips of linked wire-end ferrules | Crimping range, min. | 0.5 mm <sup>2</sup> |
| Crimping range, max. | 2.5 mm <sup>2</sup>                |                      |                     |

**Tool data - crimping**

|                          |                      |                          |                     |
|--------------------------|----------------------|--------------------------|---------------------|
| Crimping profile 1, min. | 0.5 mm <sup>2</sup>  | Crimping type/profile    | Trapezoidal crimp   |
| Crimping profile 1, max. | 0.75 mm <sup>2</sup> | Crimping profile 2, min. | 1 mm <sup>2</sup>   |
| Crimping profile 2, max. | 1.5 mm <sup>2</sup>  | Crimping profile 3, min. | 2.5 mm <sup>2</sup> |

**Classifications**

|            |             |
|------------|-------------|
| eClass 6.0 | 21-04-38-90 |
|------------|-------------|

**Product information**

|                                 |  |
|---------------------------------|--|
| Descriptive text ordering data  | Additional accessories can be found in chapter J   |
| Descriptive text technical data | Only strip-type products from Weidmüller may be processed.<br>The use of wire-end ferrules on reels may lead to destruction. |

**Cutting, stripping and crimping tool  
STRIPAX PLUS 2.5 ZERT**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

